

RAPTOR®



RAPTOR Rollbar & Chassis



DESCRIPTION

A professional quality paint, ideal for use on roll bars and chassis or any vehicle surface that needs additional protection from impact, abrasion, UV, corrosion and water damage. RAPTOR Roll Bar & Chassis' advanced formula resists temperatures up to 120°C and is 5x tougher* than ordinary paints. It dries fast to give an attractive, smooth finish that has superior adhesion and resists fading from the sun. It's also self-priming, so can be used direct to most prepared metal without the need for a primer.

FEATURES

- Heat Resistant up to 120°C
- Superior UV resistance – resists fading from the sun
- 5x Tougher than ordinary paints
- Direct to metal – no need for a primer
- Clog Free Fan Nozzle – gives a smooth finish on larger areas


TECHNICAL DATA SHEET

RAPTOR Rollbar & Chassis

Product preparation - application



It is strongly recommended to use appropriate personal protection equipment during application to avoid respiratory, skin and eye irritation.



Clean and degrease. Mask any areas as required.

Can be applied direct to metal (Bare steel, aluminium, galvanised and zinc coated sheets, stainless steel) or fully cured paint.

Sand surface with P180-P220 sandpaper and reclean. If primed, sand with P400-P600 sandpaper & reclean. If sound cured paint, sand surface with P800-P1000 sandpaper and reclean.

Thoroughly shake can for at least 2 mins before use.

Always wear safety goggles and gloves before spraying.


Use only outdoors or in a well-ventilated area.



Ready to use



Not applicable



2 - 3 coats sprayed 15-25cm away from the object

with intermediate flash-off: 10 min at 20°C

Handleable: 30 min at 20°C depending on film build

Final airdry time: 2 hr at 20°C depending on film build

VOC compliant

2004/42/IB/e(840) 724: The EU limit value for this product (product category: e) in ready to use form is maximum 840 g/l of VOC. The VOC content of this product in ready to use form is maximum 724 g/l.

TECHNICAL DATA SHEET


RAPTOR Rollbar & Chassis

Products


RRBGB/AL RAPTOR® Rollbar & Chassis Gloss Black
RRBSB/AL RAPTOR® Rollbar & Chassis Satin Black



20 - 30 µm 2 coats



RAPTOR® Rollbar & Chassis can be overcoated with itself within 4 hours, without the need for sanding, after this wait 24h for paint to cure then abrade with P800-P1000, degrease then re-apply.



After use, hold aerosol can upside down and spray briefly to clean nozzle.
Do not stick pins into the orifice.
If the nozzle becomes blocked, remove from the can and soak in gentle thinners before replacing.

Waste treatment

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Remarks

- Theoretical coverage 1.2m² per unit, assuming 100% transfer efficiency at the recommended film build.
- Aerosol cans should be stored for 2 hours at room temperature before use. For long term storage keep in a dry well ventilated area and away from direct sunlight and frost. Recommended storage temperature 5 - 25°C, recommended application temperature 20°C

Consult Safety Data Sheet prior to use. Observe the precautionary notices displayed on the container.

All other products referred to in the refinish build up are from our brand product range. System properties will not be valid when the related material is used in combination with any other materials or additives which are not part of our brand product range, unless explicitly indicated otherwise.

For professional use only! The information provided in this documentation has been carefully selected and arranged by us. It is based upon our best knowledge on the subject at the date of issuance. The Information is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check the information with regard to up-to-dateness and suitability for his intended purpose. The intellectual property in this Information, including patents, trademarks and copyrights, is protected. All rights reserved. The relevant Material Safety Data Sheet and Warnings displayed on the product label need to be observed. We may modify and/ or discontinue operation of all or portions of this Information at any time in our sole discretion, without notice and assume no responsibility to update the Information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.