



DRIVING SURFACE PERFECTION

# UP4903 RAPTOR 1K Touch Up Paint Universal Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
SDS ID: R1KTPUB-US-SDS  
Issue date: 11/2/2021 Version: 1.0

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Trade name : UP4903 RAPTOR 1K Touch Up Paint Universal Black  
Product code : UP4903  
UP Number : UP4903

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Coatings and paints, thinners, paint removers

#### 1.3. Supplier

U-POL US Inc Inc.  
108 Commerce Way  
Easton, Pennsylvania, PA 18083  
United States  
T 1-800-340-7824 - F 1-800-787-5150  
[technicalsupport@u-pol.com](mailto:technicalsupport@u-pol.com) - [www.u-pol.com](http://www.u-pol.com)

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC - 1-800-424-9300

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Flammable aerosol Category 1	Extremely flammable aerosol
Gases under pressure Liquefied gas	Contains gas under pressure; may explode if heated
Serious eye damage/eye irritation Category 1	Causes serious eye damage
Skin sensitization, Category 1	May cause an allergic skin reaction
Carcinogenicity Category 2	Suspected of causing cancer
Specific target organ toxicity — Single exposure, Category 3, Narcosis	May cause drowsiness or dizziness

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) : 

Signal word (GHS US) : Danger  
Hazard statements (GHS US) : Extremely flammable aerosol  
Contains gas under pressure; may explode if heated  
May cause an allergic skin reaction  
Causes serious eye damage  
May cause drowsiness or dizziness  
Suspected of causing cancer

Precautionary statements (GHS US) : If medical advice is needed, have product container or label at hand.  
Keep out of reach of children.

# UP4903 RAPTOR 1K Touch Up Paint Universal Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Do not spray on an open flame or other ignition source.  
Pressurized container: Do not pierce or burn, even after use.  
Avoid breathing vapors, spray, fume.  
Use only outdoors or in a well-ventilated area.  
Contaminated work clothing must not be allowed out of the workplace.  
Wear eye protection, protective clothing, protective gloves.  
If on skin: Wash with plenty of water.  
If inhaled: Remove person to fresh air and keep comfortable for breathing.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If exposed or concerned: Get medical advice/attention.  
Call a doctor if you feel unwell.  
If skin irritation or rash occurs: Get medical advice/attention.  
Wash contaminated clothing before reuse.  
Store in a well-ventilated place. Keep container tightly closed.  
Store locked up.  
Protect from sunlight. Store in a well-ventilated place.  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

5.56% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapors))

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
acetone	CAS-No.: 67-64-1	5 – 23	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
n-butyl acetate	CAS-No.: 123-86-4	5 – 23	Flam. Liq. 3, H226 STOT SE 3, H336
cyclohexanone	CAS-No.: 108-94-1	5 – 23	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Dam. 1, H318
ethyl methyl ketone	CAS-No.: 78-93-3	5 – 23	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

# UP4903 RAPTOR 1K Touch Up Paint Universal Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
methyl acetate	CAS-No.: 79-20-9	< 5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
carbon black	CAS-No.: 1333-86-4	< 5	Carc. 2, H351
reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	CAS No.: 1064698-37-8	< 5	Skin Sens. 1A, H317 Aquatic Chronic 2, H411

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Specific hazards arising from the chemical

Fire hazard	: Extremely flammable aerosol.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

# UP4903 RAPTOR 1K Touch Up Paint Universal Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing fume, mist, spray, vapors. Avoid contact with skin and eyes.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product. Notify authorities if product enters sewers or public waters.  
Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing fume, mist, spray, vapors. Avoid contact with skin and eyes.

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Keep container tightly closed. Keep cool.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### UP4903 RAPTOR 1K Touch Up Paint Universal Black

No additional information available

##### ethyl methyl ketone (78-93-3)

##### USA - ACGIH - Occupational Exposure Limits

Local name	Methyl ethyl ketone (MEK)
ACGIH OEL TWA [ppm]	200 ppm
ACGIH OEL STEL [ppm]	300 ppm

# UP4903 RAPTOR 1K Touch Up Paint Universal Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>ethyl methyl ketone (78-93-3)</b>	
Remark (ACGIH)	TLV® Basis: URT irr; CNS & PNS impair. Notations: BEI
Regulatory reference	ACGIH 2021
<b>USA - ACGIH - Biological Exposure Indices</b>	
Local name	METHYL ETHYL KETONE
BEI (BLV)	2 mg/l Parameter: Methyl ethyl ketone - Medium: urine - Sampling time: End of shift - Notations: Ns
Regulatory reference	ACGIH 2021
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	2-Butanone (Methyl ethyl ketone)
OSHA PEL (TWA) [1]	590 mg/m <sup>3</sup>
OSHA PEL (TWA) [2]	200 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>methyl acetate (79-20-9)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Methyl acetate
ACGIH OEL TWA [ppm]	200 ppm
ACGIH OEL STEL [ppm]	250 ppm
Remark (ACGIH)	TLV® Basis: Headache; dizziness; nausea; eye dam (degeneration of ganglion cells in the retina)
Regulatory reference	ACGIH 2021
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Methyl acetate
OSHA PEL (TWA) [1]	610 mg/m <sup>3</sup>
OSHA PEL (TWA) [2]	200 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>n-butyl acetate (123-86-4)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	n-Butyl acetate
ACGIH OEL TWA [ppm]	50 ppm
ACGIH OEL STEL [ppm]	150 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr
Regulatory reference	ACGIH 2021
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	n-Butyl-acetate
OSHA PEL (TWA) [1]	710 mg/m <sup>3</sup>
OSHA PEL (TWA) [2]	150 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

# UP4903 RAPTOR 1K Touch Up Paint Universal Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>cyclohexanone (108-94-1)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Cyclohexanone
ACGIH OEL TWA [ppm]	20 ppm
ACGIH OEL STEL [ppm]	50 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2021
<b>USA - ACGIH - Biological Exposure Indices</b>	
Local name	CYCLOHEXANONE
BEI (BLV)	80 mg/l Parameter: 1,2-Cyclohexanediol (with hydrolysis) - Medium: urine - Sampling time: End of shift at end of workweek - Notations: Ns, Sq 8 mg/l Parameter: Cyclohexanol (with hydrolysis) - Medium: urine - Sampling time: End of shift - Notations: Ns, Sq
Regulatory reference	ACGIH 2021
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Cyclohexanone
OSHA PEL (TWA) [1]	200 mg/m <sup>3</sup>
OSHA PEL (TWA) [2]	50 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>reaction mass of <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-hydroxypoly(oxyethylene) and <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)</b>	
No additional information available	
<b>carbon black (1333-86-4)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Carbon black
ACGIH OEL TWA	3 mg/m <sup>3</sup> (Inhalable fraction)
Remark (ACGIH)	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2021
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Carbon black
OSHA PEL (TWA) [1]	3.5 mg/m <sup>3</sup>
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>acetone (67-64-1)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Acetone
ACGIH OEL TWA [ppm]	250 ppm
ACGIH OEL STEL [ppm]	500 ppm

# UP4903 RAPTOR 1K Touch Up Paint Universal Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

acetone (67-64-1)	
Remark (ACGIH)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2021
USA - ACGIH - Biological Exposure Indices	
Local name	ACETONE
BEI (BLV)	25 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift - Notations: Ns
Regulatory reference	ACGIH 2021
USA - OSHA - Occupational Exposure Limits	
Local name	Acetone
OSHA PEL (TWA) [1]	2400 mg/m <sup>3</sup>
OSHA PEL (TWA) [2]	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

<b>Hand protection:</b>
Protective gloves
<b>Eye protection:</b>
Safety glasses
<b>Skin and body protection:</b>
Wear suitable protective clothing
<b>Respiratory protection:</b>
In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : aerosol.  
Color : Black  
Odor : Solvent-like odour  
Odor threshold : No data available  
pH : No data available

# UP4903 RAPTOR 1K Touch Up Paint Universal Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.788 g/cm <sup>3</sup>
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

VOC content	: 695.36 g/l
As Packaged Regulatory VOC	: 659 g/l (5.5 lbs gal)
As Packaged Actual VOC	: 528 g/l (4.4 lbs gal)
As Applied Regulatory VOC	: 659 g/l (5.5 lbs gal)
As Applied Actual VOC	: 528 g/l (4.4 lbs gal)
Percent Solids	: 12.98 wt%
Percent Solids	: 9.38 vol %
Volatiles	: 87.0 wt%
Water Content	: 0 wt%
Water Content	: 0 vol %
Exempt Compounds by weight	: 20.0 wt%
Exempt Compounds by volume	: 19.9 vol %
% EPA HAPS	: 7.6 wt%
Maximum Incremental Reactivity (MIR)	: 0.68
MIR EPA Aerosol Category	: Non-Flat Coating - NFP 1.4
MIR CARB Aerosol Category	: Nonflat Coating - General Coatings - NFP 0.95
Bay Area Aerosol Category	: General Coatings - Non-Flat Paint Products - max. 65% VOC

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Extremely flammable aerosol.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.



# UP4903 RAPTOR 1K Touch Up Paint Universal Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### UP4903 RAPTOR 1K Touch Up Paint Universal Black

Unknown acute toxicity (GHS US)	5.56% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapors))
---------------------------------	--

#### ethyl methyl ketone (78-93-3)

LD50 oral rat	2193 mg/kg body weight (Equivalent or similar to OECD 423, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 10 ml/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))
ATE US (oral)	2193 mg/kg body weight

#### methyl acetate (79-20-9)

LD50 oral rat	6482 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	49 mg/l
ATE US (oral)	6482 mg/kg body weight
ATE US (vapors)	49 mg/l/4h
ATE US (dust, mist)	49 mg/l/4h

#### n-butyl acetate (123-86-4)

LD50 oral rat	10760 – 12789 mg/kg body weight (Equivalent or similar to OECD 423, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 14112 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	23.4 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Inhalation (mixture of vapour and aerosol), 14 day(s))
LC50 Inhalation - Rat [ppm]	390 ppm/4h
ATE US (oral)	10760 mg/kg body weight
ATE US (gases)	390 ppmV/4h
ATE US (vapors)	23.4 mg/l/4h
ATE US (dust, mist)	23.4 mg/l/4h

# UP4903 RAPTOR 1K Touch Up Paint Universal Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>cyclohexanone (108-94-1)</b>	
LD50 oral rat	1890 – 2650 mg/kg body weight (BASF test, Rat, Experimental value, Oral, 7 day(s))
LD50 dermal rabbit	1100 mg/kg (BRENNTAG test)
LC50 Inhalation - Rat	> 6.2 mg/l air Animal: rat
ATE US (oral)	1890 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
<b>reaction mass of <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-hydroxypoly(oxyethylene) and <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)</b>	
LD50 oral rat	> 5000 mg/kg (OECD Guideline No. 401 (equivalent to Annex V), limit test, rat, male/female)
LD50 dermal rat	> 2000 mg/kg (OECD Guideline No. 402 (equivalent to Annex V), limit test, rat, male/female)
LC50 Inhalation - Rat	5800 mg/l (OECD Guideline 403, 14d, rat)
ATE US (vapors)	5800 mg/l/4h
ATE US (dust, mist)	5800 mg/l/4h
<b>carbon black (1333-86-4)</b>	
LD50 oral rat	> 8000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LC50 Inhalation - Rat	> 4.6 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Experimental value, Inhalation (dust))
<b>acetone (67-64-1)</b>	
LD50 oral rat	5800 mg/kg body weight Animal: rat, Animal sex: female
LD50 dermal rabbit	> 15800 mg/kg body weight (24 h, Rabbit, Male, Weight of evidence, Dermal, 14 day(s))
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4
ATE US (oral)	5800 mg/kg body weight
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
<b>cyclohexanone (108-94-1)</b>	
IARC group	3 - Not classifiable
<b>carbon black (1333-86-4)</b>	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: Not classified
<b>acetone (67-64-1)</b>	
LOAEL (animal/female, F0/P)	11298 mg/kg body weight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg body weight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)

# UP4903 RAPTOR 1K Touch Up Paint Universal Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

STOT-single exposure : May cause drowsiness or dizziness.

<b>ethyl methyl ketone (78-93-3)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>methyl acetate (79-20-9)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>n-butyl acetate (123-86-4)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>acetone (67-64-1)</b>	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

<b>methyl acetate (79-20-9)</b>	
LOAEC (inhalation, rat, vapor, 90 days)	2000 mg/l
NOAEC (inhalation, rat, vapor, 90 days)	1057 mg/m <sup>3</sup>
<b>cyclohexanone (108-94-1)</b>	
NOAEL (oral, rat, 90 days)	143 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Aspiration hazard : Not classified  
Viscosity, kinematic : No data available  
Symptoms/effects : May cause drowsiness or dizziness.  
Symptoms/effects after skin contact : May cause an allergic skin reaction.  
Symptoms/effects after eye contact : Serious damage to eyes.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

<b>ethyl methyl ketone (78-93-3)</b>	
LC50 - Fish [1]	2993 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	308 mg/l Test organisms (species): Daphnia magna
ErC50 algae	1972 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)
<b>methyl acetate (79-20-9)</b>	
LC50 - Fish [1]	250 – 350 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	1026.7 mg/l Test organisms (species): Daphnia magna
<b>n-butyl acetate (123-86-4)</b>	
LC50 - Fish [1]	18 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	44 mg/l Test organisms (species): Daphnia sp.
LC50 - Fish [2]	62 mg/l (Leuciscus idus, static system)
ErC50 algae	397 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Read-across, GLP)

# UP4903 RAPTOR 1K Touch Up Paint Universal Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>n-butyl acetate (123-86-4)</b>	
NOEC (chronic)	23 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic crustacea	23 mg/l
<b>cyclohexanone (108-94-1)</b>	
LC50 - Fish [1]	527 – 732 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
ErC50 algae	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Read-across, GLP)
<b>reaction mass of <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-hydroxypoly(oxyethylene) and <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)</b>	
LC50 - Fish [1]	2.8 mg/l (96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	4 mg/l (48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
ErC50 algae	> 100 mg/l (72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
<b>carbon black (1333-86-4)</b>	
LC50 - Fish [1]	> 1000 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	> 5600 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 24 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	> 10000 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)
<b>acetone (67-64-1)</b>	
LC50 - Fish [1]	6210 – 8120 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Measured concentration)
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	$\geq$ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
<b>12.2. Persistence and degradability</b>	
<b>ethyl methyl ketone (78-93-3)</b>	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	2.03 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.31 g O <sub>2</sub> /g substance
ThOD	2.44 g O <sub>2</sub> /g substance
<b>methyl acetate (79-20-9)</b>	
Persistence and degradability	Readily biodegradable in water.
<b>n-butyl acetate (123-86-4)</b>	
Persistence and degradability	Readily biodegradable in water.

# UP4903 RAPTOR 1K Touch Up Paint Universal Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>n-butyl acetate (123-86-4)</b>	
ThOD	2.21 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.46
<b>cyclohexanone (108-94-1)</b>	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.232 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.605 g O <sub>2</sub> /g substance
ThOD	2.605 g O <sub>2</sub> /g substance
<b>carbon black (1333-86-4)</b>	
Persistence and degradability	Biodegradability in soil: not applicable. Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
<b>acetone (67-64-1)</b>	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.43 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.92 g O <sub>2</sub> /g substance
ThOD	2.2 g O <sub>2</sub> /g substance
<b>12.3. Bioaccumulative potential</b>	
<b>ethyl methyl ketone (78-93-3)</b>	
Partition coefficient n-octanol/water (Log Pow)	0.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 40 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>methyl acetate (79-20-9)</b>	
BCF - Fish [1]	< 1 (Pisces, Literature study)
Partition coefficient n-octanol/water (Log Pow)	0.18 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>n-butyl acetate (123-86-4)</b>	
Partition coefficient n-octanol/water (Log Pow)	2.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>cyclohexanone (108-94-1)</b>	
Partition coefficient n-octanol/water (Log Pow)	0.86 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

# UP4903 RAPTOR 1K Touch Up Paint Universal Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>reaction mass of <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-hydroxypoly(oxyethylene) and <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)</b>	
BCF - Fish [1]	2658 – 3430 (502 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	4.6 (Experimental value, Equivalent or similar to OECD 117, 25 °C)
<b>carbon black (1333-86-4)</b>	
Bioaccumulative potential	Not bioaccumulative.
<b>acetone (67-64-1)</b>	
Partition coefficient n-octanol/water (Log Pow)	-0.23 (Test data)
Bioaccumulative potential	Not bioaccumulative.
<b>12.4. Mobility in soil</b>	
<b>ethyl methyl ketone (78-93-3)</b>	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.654 – 1.281 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil. Slightly harmful to plants.
<b>methyl acetate (79-20-9)</b>	
Surface tension	24 mN/m (20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
Ecology - soil	Highly mobile in soil.
<b>n-butyl acetate (123-86-4)</b>	
Surface tension	61.3 mN/m (20 °C, 0.1 %, OECD 115: Surface Tension of Aqueous Solutions)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.268 – 1.844 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.
<b>cyclohexanone (108-94-1)</b>	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.18 (log Koc, SRC PCKOCWIN v1.66, Calculated value)
Ecology - soil	Highly mobile in soil.
<b>carbon black (1333-86-4)</b>	
Surface tension	Not applicable (solid)
Ecology - soil	No (test)data on mobility of the substance available. Not toxic to plants. Not toxic to animals.
<b>acetone (67-64-1)</b>	
Surface tension	23300 mN/m (20 °C)

# UP4903 RAPTOR 1K Touch Up Paint Universal Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

acetone (67-64-1)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

### 14.1. UN number

DOT NA No : UN1950  
UN-No. (TDG) : UN1950  
UN-No. (IMDG) : 1950  
UN-No. (IATA) : 1950

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Aerosols  
Proper Shipping Name (TDG) : AEROSOLS  
Proper Shipping Name (IMDG) : AEROSOLS  
Proper Shipping Name (IATA) : Aerosols, flammable

### 14.3. Transport hazard class(es)

#### DOT

Transport hazard class(es) (DOT) : 2.1  
Hazard labels (DOT) : 2.1

#### TDG

Transport hazard class(es) (TDG) : 2.1  
Hazard labels (TDG) : 2.1

#### IMDG

Transport hazard class(es) (IMDG) : 2.1  
Hazard labels (IMDG) : 2.1



#### IATA

Transport hazard class(es) (IATA) : 2.1  
Hazard labels (IATA) : 2.1

# UP4903 RAPTOR 1K Touch Up Paint Universal Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



### 14.4. Packing group

Packing group (DOT)	: Not applicable
Packing group (TDG)	: Not applicable
Packing group (IMDG)	: Not applicable
Packing group (IATA)	: Not applicable

### 14.5. Environmental hazards

Other information	: No supplementary information available.
-------------------	---

### 14.6. Special precautions for user

<b>DOT</b>	
UN-No.(DOT)	: UN1950
DOT Special Provisions (49 CFR 172.102)	: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Packaging Non Bulk (49 CFR 173.xxx)	: None
DOT Packaging Bulk (49 CFR 173.xxx)	: None
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 25 - Protected from sources of heat,87 - Stow "separated from" Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials
<b>TDG</b>	
UN-No. (TDG)	: UN1950
TDG Special Provisions	: 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment),107 - (1) These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL. (2) Subsection (1) does not apply to self-defence spray.
Explosive Limit and Limited Quantity Index	: 1 L
Excepted quantities (TDG)	: E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 75 L
Emergency Response Guide (ERG) Number	: 126
<b>IMDG</b>	
Special provision (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	: S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	: None



# UP4903 RAPTOR 1K Touch Up Paint Universal Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### IATA

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provision (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
ethyl methyl ketone	78-93-3	Present	Active	XU
methyl acetate	79-20-9	Present	Active	XU
n-butyl acetate	123-86-4	Present	Active	XU
cyclohexanone	108-94-1	Present	Active	XU
carbon black	1333-86-4	Present	Active	PMN
acetone	67-64-1	Present	Active	PMN

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

#### ethyl methyl ketone (78-93-3)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	5000 lb
-----------	---------

#### n-butyl acetate (123-86-4)

CERCLA RQ	5000 lb
-----------	---------

#### cyclohexanone (108-94-1)

CERCLA RQ	5000 lb
-----------	---------

#### acetone (67-64-1)

CERCLA RQ	5000 lb
-----------	---------

# UP4903 RAPTOR 1K Touch Up Paint Universal Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 15.2. International regulations

#### CANADA

##### ethyl methyl ketone (78-93-3)

Listed on the Canadian DSL (Domestic Substances List)

##### methyl acetate (79-20-9)

Listed on the Canadian DSL (Domestic Substances List)

##### n-butyl acetate (123-86-4)

Listed on the Canadian DSL (Domestic Substances List)

##### cyclohexanone (108-94-1)

Listed on the Canadian DSL (Domestic Substances List)

##### carbon black (1333-86-4)

Listed on the Canadian DSL (Domestic Substances List)

##### acetone (67-64-1)

Listed on the Canadian DSL (Domestic Substances List)

#### EU-Regulations

No additional information available

#### National regulations

##### n-butyl acetate (123-86-4)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

##### carbon black (1333-86-4)

Listed on IARC (International Agency for Research on Cancer)  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

##### acetone (67-64-1)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

### 15.3. US State regulations

#### WARNING:

This product can expose you to ethylbenzene, which is known to the State of California to cause cancer, and toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Component	State or local regulations
ethyl methyl ketone(78-93-3)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List

# UP4903 RAPTOR 1K Touch Up Paint Universal Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Component	State or local regulations
methyl acetate(79-20-9)	U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. – New York City – Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
n-butyl acetate(123-86-4)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. – New York City – Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
cyclohexanone(108-94-1)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. – New York City – Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
carbon black(1333-86-4)	U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
acetone(67-64-1)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. – New York City – Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List

### SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at [WWW.U-POL.COM](http://WWW.U-POL.COM).