## Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

Issue date: 8/2/2023 Version: 1.0

## **SECTION 1: Identification**

#### 1.1 Product identifier

RAPTOR CALIPER ENAMEL REAL RED Trade name

Product form Mixture

Type of product Coatings and paints, thinners, paint removers

Product code RCERR/AL

## 1.2 Other means of identification

No additional information available

#### 1.3 Recommended use of the chemical and restrictions on use

Recommended use : Coatings and paints, thinners, paint removers

## 1.4 Details of manufacturer or importer

#### Distributor

U-POL New Zealand Limited Ltd

c/o Lindsay & Associates Unit H, 12 Amera Place, East Tamaki

Manukau City Auckland 2013

New Zealand

T + 612 4731 2655 / 027 630 3691 - F + 612 4731 2611

info@u-pol.co.nz - www.u-pol.com

## 1.5. Emergency phone number

Emergency number : Australia (CHEMTREC): + (61) - 290372994

## **SECTION 2: Hazard identification**

## 2.1. Classification of the hazardous chemical

**HSNO** Approval Number : HSR002517

#### Classification according to the Environmental Protection Authority notices (EPA Hazardous Substances and New Organisms Act 1996)

Aerosol, Category 1 H222 H319 Serious eye damage/eye irritation, Category 2 Reproductive toxicity, Category 2 H361 Specific target organ toxicity - Single exposure, Category 3, Narcosis H336 Specific target organ toxicity - Repeated exposure, Category 2 H373

## 2.2. GHS Label elements, including precautionary statements

#### **GHS NZ labelling**

Hazard pictograms (GHS NZ)







Signal word (GHS NZ)

Danger

Contains methyl acetate (23 - 43 %); n-butyl acetate (5 - 23 %); Xylene (< 5 %); ethylbenzene (< 5

%); hexanoic acid, 2-ethyl-, zinc salt, basic (< 5 %)

Hazard statements (GHS NZ)

H222 - Extremely flammable aerosol H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H361 - Suspected of damaging fertility or the unborn child

H373 - May cause damage to organs through prolonged or repeated exposure

## Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

Precautionary statements : P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

Prevention P103 - Read carefully and follow all instructions.

Prevention : P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.
P260 - Do not breathe fume, spray, vapours.
P264 - Wash hands thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear eye protection, protective clothing, protective gloves.

Response : P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P308+P313 - IF exposed or concerned: Get medical advice. P337+P313 - If eye irritation persists: Get medical advice.

Storage : P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Disposal : P501 - Dispose of contents and container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

#### 2.3. Other hazards which do not result in classification

No additional information available

## **SECTION 3: Composition and information on ingredients**

## 3.1. Substances

Not applicable

#### 3.2. Mixtures

| Name           | Product identifier | %       | Classification according to GHS NZ   |
|----------------|--------------------|---------|--|
| methyl acetate | CAS-No.: 79-20-9   | 23 – 43 | Flam. Liq. 2, H225<br>Eye Irrit. 2, H319<br>STOT SE 3, H336  |
| Xylene         | CAS-No.: 1330-20-7 | < 5     | Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 |
| ethylbenzene   | CAS-No.: 100-41-4  | < 5     | Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 3, H412  |

## Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

| Name                                      | Product identifier  | %   | Classification according to GHS NZ  |
|---|---------------------|-----|---|
| hexanoic acid, 2-ethyl-, zinc salt, basic | CAS-No.: 85203-81-2 | < 5 | Eye Irrit. 2, H319<br>Repr. 2, H361<br>Aquatic Acute 3, H402<br>Aquatic Chronic 3, H412 |

## **SECTION 4: First-aid measures**

## 4.1. Description of necessary first-aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

## 4.2. Symptoms caused by exposure

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after eye contact : Eye irritation.

#### 4.3. Medical attention and special treatment

Other medical advice or treatment : Treat symptomatically.

## **SECTION 5: Fire-fighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

## 5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

## 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe fume,

spray, vapours. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

## 6.2. Environmental precautions

Avoid release to the environment.

8/2/2023 (Issue date) NZ - en 3/13

## Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

## 6.3. Methods and materials for containment and cleaning up

Methods for cleaning up

: Mechanically recover the product. Notify authorities if product enters sewers or public waters.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe fume, spray, vapours. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.

Hygiene measures

Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

## 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

## **SECTION 8: Exposure controls and personal protection**

#### 8.1. Control parameters - exposure standards

| Xylene (1330-20-7)                         |  |  |  |  |
|--|--|--|--|--|
| New Zealand - Occupational Exposure Limits |  |  |  |  |
| Local name                                 | Xylene (Dimethylbenzene)   |  |  |  |
| WES-TWA (OEL TWA) [1]                      | 217 mg/m³  |  |  |  |
| WES-TWA (OEL TWA) [2]                      | 50 ppm   |  |  |  |
| Regulatory reference                       | Workplace Exposure Standards and Biological Exposure Indices, 12th Edition   |  |  |  |
| New Zealand - Biological Exposure Indices  |  |  |  |  |
| Local name                                 | Xylene   |  |  |  |
| BEI  | 1.5 g/l Parameter: Methylhippuric acid - Medium: Urine - Sampling time: End of shift   |  |  |  |
| Regulatory reference                       | Workplace Exposure Standards and Biological Exposure Indices, 12th Edition   |  |  |  |
| ethylbenzene (100-41-4)                    |  |  |  |  |
| New Zealand - Occupational Exposure Limits |  |  |  |  |
| Local name                                 | Ethyl benzene  |  |  |  |
| WES-TWA (OEL TWA) [1]                      | 434 mg/m³  |  |  |  |
| WES-TWA (OEL TWA) [2]                      | 100 ppm  |  |  |  |
| WES-STEL (OEL STEL)                        | 543 mg/m³  |  |  |  |
| WES-STEL (OEL STEL) [ppm]                  | 125 ppm  |  |  |  |
| Regulatory reference                       | Workplace Exposure Standards and Biological Exposure Indices, 12th Edition   |  |  |  |
| New Zealand - Biological Exposure Indices  |  |  |  |  |
| Local name                                 | Ethyl benzene  |  |  |  |
| BEI  | 0.25 g/g creatinine Parameter: Sum of mandelic acid and phenylglyoxylic acids - Medium: Urine - Sampling time: End of shift or end of exposure |  |  |  |
| Regulatory reference                       | Workplace Exposure Standards and Biological Exposure Indices, 12th Edition   |  |  |  |

## Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

| methyl acetate (79-20-9)                   |  |  |
|--|--|--|
| New Zealand - Occupational Exposure Limits |  |  |
| Local name                                 | Methyl acetate   |  |
| WES-TWA (OEL TWA) [1]                      | 606 mg/m³  |  |
| WES-TWA (OEL TWA) [2]                      | 200 ppm  |  |
| WES-STEL (OEL STEL)                        | 757 mg/m³  |  |
| WES-STEL (OEL STEL) [ppm]                  | 250 ppm  |  |
| Regulatory reference                       | Workplace Exposure Standards and Biological Exposure Indices, 12th Edition |  |

#### Exposure limit values for the other components

No additional information available

#### 8.2. Monitoring methods

No additional information available

## 8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

#### 8.4. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Protective gloves
Eye protection : Safety glasses

Skin and body protection : Wear suitable protective clothing

Respiratory protection : [In case of inadequate ventilation] wear respiratory protection.

## Personal protective equipment symbol(s)







Environmental exposure controls : Avoid release to the environment.

## **SECTION 9: Physical and chemical properties**

Physical state : Liquid
Appearance : Liquid.
Colour : Red
Odour : characteristic

Odour threehold

Odour threshold : No additional information available pH : No additional information available Evaporation rate : No additional information available

Relative evaporation rate (butylacetate=1) : No data available

Melting point / Freezing point : No additional information available

Boiling point : No data available

Flash point : -41 °C

Auto-ignition temperature : No data available

Flammability : Extremely flammable aerosol.

Vapour pressure : No additional information available

Relative density : No additional information available

Density: 0.808 g/cm³

Solubility : No additional information available

Partition coefficient n-octanol/water (Log Pow) : No data available Viscosity, dynamic : No data available

Explosive properties : Pressurised container: May burst if heated.

Explosive limits : No additional information available

Minimum ignition energy : No data available

VOC content : 673 g/l

8/2/2023 (Issue date) NZ - en 5/13

## Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

Percent Solids : 10.34 wt%

## **SECTION 10: Stability and reactivity**

Reactivity : Extremely flammable aerosol. Pressurised container: May burst if heated.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No dangerous reactions known under normal conditions of use.

Conditions to avoid : Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of

ignition.

Incompatible materials : No additional information available

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not

be produced.

## **SECTION 11: Toxicological information**

| - | _ | M | u | 7.4 | 16. | w |
|---|---|---|---|-----|-----|---|

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

| Acute toxicity (inhalation)               | : Not classified   |
|---|--|
| Xylene (1330-20-7)                        |  |
| LD50 oral rat                             | > 4000 mg/kg bodyweight (Equivalent or similar to EU Method B.1, Rat, Female, Experimental value, Oral, 14 day(s))                             |
| LD50 dermal rat                           | 12126 mg/kg (Non-GLP, read-across from supporting substance, single dermal dose under occlusion followed by observation for 14 days)           |
| LD50 dermal rabbit                        | 12126 mg/kg bodyweight Animal: rabbit, Animal sex: male  |
| LC50 Inhalation - Rat                     | 29.09 mg/l (Equivalent or similar to EU Method B.2, 4 h, Rat, Male, Experimental value, Inhalation (vapours), 14 day(s))                       |
| LC50 Inhalation - Rat [ppm]               | 6700 ppm/4h (EU Method B.2 (Acute Toxicity (Inhalation)), 4h, rat, male)   |
| ethylbenzene (100-41-4)                   |  |
| LD50 oral rat                             | 3500 mg/kg (Rat, Male / female, Experimental value, Oral, 14 day(s))   |
| LD50 dermal rabbit                        | 15433 mg/kg bodyweight (24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))   |
| LC50 Inhalation - Rat                     | 17.8 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours), 14 day(s))  |
| methyl acetate (79-20-9)                  |  |
| LD50 oral rat                             | 6482 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)                                       |
| LD50 dermal rat                           | > 2000 mg/kg bodyweight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: OECD Guideline 402 (Acute Dermal Toxicity) |
| LC50 Inhalation - Rat                     | 49 mg/l  |
| hexanoic acid, 2-ethyl-, zinc salt, basic | (85203-81-2)   |
| LD50 oral rat                             | > 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)   |
| LD50 dermal rat                           | > 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)   |
| LC50 Inhalation - Rat                     | > 5.7 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)  |
| Skin corrosion/irritation                 | : Not classified   |

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

# Safety Data Sheet

| according to the | Hazardous | Substances | and New | Organisms Act | (1996) |
|------------------|-----------|------------|---------|---------------|--------|
|                  |           |            |         |               |        |

| according to the Hazardous Substances and New Organisms A | CT (1996)   |  |  |  |
|---|---|--|--|--|
| •   | Suspected of damaging fertility or the unborn child.  May cause drowsiness or dizziness.  |  |  |  |
| Xylene (1330-20-7)  |   |  |  |  |
| STOT-single exposure                                      | May cause respiratory irritation.   |  |  |  |
| methyl acetate (79-20-9)                                  |   |  |  |  |
| STOT-single exposure                                      | May cause drowsiness or dizziness.  |  |  |  |
| STOT-repeated exposure :                                  | May cause damage to organs through prolonged or repeated exposure.  |  |  |  |
| Xylene (1330-20-7)  |   |  |  |  |
| LOAEL (oral, rat, 90 days)                                | 150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)     |  |  |  |
| STOT-repeated exposure                                    | May cause damage to organs through prolonged or repeated exposure.  |  |  |  |
| ethylbenzene (100-41-4)                                   |   |  |  |  |
| NOAEL (oral, rat, 90 days)                                | 75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-<br>Day Oral Toxicity in Rodents)  |  |  |  |
| STOT-repeated exposure                                    | May cause damage to organs through prolonged or repeated exposure.  |  |  |  |
| methyl acetate (79-20-9)                                  |   |  |  |  |
| LOAEC (inhalation, rat, vapour, 90 days)                  | 2000 mg/l   |  |  |  |
| NOAEC (inhalation, rat, vapour, 90 days)                  | 1057 mg/m³  |  |  |  |
| hexanoic acid, 2-ethyl-, zinc salt, basic (85203-81-2)    |   |  |  |  |
| NOAEL (subchronic, oral, animal/male, 90 days)            | 180 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: other:TSCA (1992) health Effects Testing Guidelines for Subchronic Oral Toxicity Studies. Title 40, CFR 798. 2650.   |  |  |  |
| NOAEL (subchronic, oral, animal/female, 90 days)          | 205 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: other:TSCA (1992) health Effects Testing Guidelines for Subchronic Oral Toxicity Studies. Title 40, CFR 798. 2650. |  |  |  |
| Aspiration hazard :                                       | Not classified  |  |  |  |
| RAPTOR CALIPER ENAMEL REAL RED                            |   |  |  |  |
| Vaporizer   | Aerosol   |  |  |  |
| Xylene (1330-20-7)  |   |  |  |  |
| Viscosity, kinematic                                      | 0.74 mm²/s (20 °C)  |  |  |  |
| Hydrocarbon   | Yes   |  |  |  |
| ethylbenzene (100-41-4)                                   | ethylbenzene (100-41-4)   |  |  |  |
| Viscosity, kinematic                                      | 0.773 mm²/s (20 °C, OECD 114: Viscosity of Liquids)   |  |  |  |
| Hydrocarbon   | Yes   |  |  |  |
| methyl acetate (79-20-9)                                  |   |  |  |  |
| Viscosity, kinematic                                      | No data available in the literature   |  |  |  |
|   |   |  |  |  |

## SECTION 12: Ecological information

## 12.1. Ecotoxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse

effects in the environment.

Hazardous to the aquatic environment, short-term

(acute)

: Not classified

# Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

Hazardous to the aquatic environment, long-term : Not classified

(chronic)

Soil toxicity : Not classified
Terrestrial vertebrate toxicity : Not classified
Terrestrial invertebrate toxicity : Not classified

| Terrestrial invertebrate toxicity :                        | Not classified   |
|--|--|
| Xylene (1330-20-7)   |  |
| LC50 - Fish [1]  | 2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)  |
| EC50 - Crustacea [1]                                       | > 3.4 mg/l Test organisms (species): Ceriodaphnia dubia  |
| EC50 72h - Algae [1]                                       | 2.2 mg/l   |
| ErC50 algae  | 4.36 mg/l (OECD 201: Alga, Growth Inhibition Test, 73 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP) |
| NOEC chronic fish  | > 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'                                     |
| BCF - Fish [1]   | 7.2 – 25.9 (56 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Readacross)  |
| Partition coefficient n-octanol/water (Log Pow)            | 3.2 (Read-across, 20 °C)   |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 2.73 (log Koc, Equivalent or similar to OECD 121, Read-across)   |
| LD50 dermal rabbit   | 12126 mg/kg bodyweight Animal: rabbit, Animal sex: male  |
|  | 12126 mg/kg (Non-GLP, read-across from supporting substance, single dermal dose under occlusion followed by observation for 14 days)           |
| LD50 oral rat  | > 4000 mg/kg bodyweight (Equivalent or similar to EU Method B.1, Rat, Female, Experimental value, Oral, 14 day(s))                             |
| ethylbenzene (100-41-4)                                    |  |
| LC50 - Fish [1]  | 5.1 mg/l Test organisms (species): Menidia menidia   |
| EC50 - Crustacea [1]                                       | 1.8 – 2.4 mg/l (US EPA, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)   |
| EC50 72h - Algae [1]                                       | 4.9 mg/l Test organisms (species): Skeletonema costatum  |
| EC50 72h - Algae [2]                                       | 5.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)       |
| LOEC (chronic)   | 1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'  |
| NOEC (chronic)   | 0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'   |
| BCF - Fish [1]   | 1 (6 week(s), Oncorhynchus kisutch, Flow-through system, Salt water, Experimental value)   |
| Partition coefficient n-octanol/water (Log Pow)            | 3.6 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)  |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 2.71 (log Koc, PCKOCWIN v1.66, QSAR)   |
| LD50 dermal rabbit   | 15433 mg/kg bodyweight (24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))   |
| LD50 oral rat  | 3500 mg/kg (Rat, Male / female, Experimental value, Oral, 14 day(s))   |
| methyl acetate (79-20-9)                                   |  |
| LC50 - Fish [1]  | 250 – 350 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)  |
| EC50 - Crustacea [1]                                       | 1026.7 mg/l Test organisms (species): Daphnia magna  |
| EC50 72h - Algae [1]                                       | > 120 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)  |
| BCF - Fish [1]   | < 1 (Pisces, Literature study)   |

# Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

| methyl acetate (79-20-9)                                   |  |
|--|--|
| Partition coefficient n-octanol/water (Log Pow)            | 0.18 (Experimental value, 20 °C)   |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP) |
|  | > 2000 mg/kg bodyweight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)                                     |
| LD50 oral rat  | 6482 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)   |
| hexanoic acid, 2-ethyl-, zinc salt, basic (85203           | I-81-2)  |
| LC50 - Fish [1]  | 100 mg/l Test organisms (species): Cyprinus carpio   |
| EC50 - Crustacea [1]                                       | 0.147 ml/l (Daphnia magna)   |
|  | > 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)   |
| LD50 oral rat  | > 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)   |

## 12.2. Persistence and degradability

| RAPTOR CALIPER ENAMEL REAL RED  |  |  |  |
|---------------------------------|--|--|--|
| Persistence and degradability   | No additional information available                        |  |  |
| Xylene (1330-20-7)              |  |  |  |
| Persistence and degradability   | Biodegradable in the soil. Readily biodegradable in water. |  |  |
| ethylbenzene (100-41-4)         |  |  |  |
| Persistence and degradability   | Biodegradable in the soil. Readily biodegradable in water. |  |  |
| Biochemical oxygen demand (BOD) | 1.44 g O₂/g substance                                      |  |  |
| Chemical oxygen demand (COD)    | 2.1 g O <sub>2</sub> /g substance                          |  |  |
| ThOD                            | 3.17 g O₂/g substance                                      |  |  |
| methyl acetate (79-20-9)        |  |  |  |
| Persistence and degradability   | Readily biodegradable in water.                            |  |  |

## 12.3. Bioaccumulative potential

| RAPTOR CALIPER ENAMEL REAL RED                                |   |  |  |
|---|---|--|--|
| Bioaccumulative potential No additional information available |   |  |  |
| Xylene (1330-20-7)  |   |  |  |
| BCF - Fish [1]  | 7.2 – 25.9 (56 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Readacross) |  |  |
| Partition coefficient n-octanol/water (Log Pow)               | 3.2 (Read-across, 20 °C)  |  |  |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc)    | 2.73 (log Koc, Equivalent or similar to OECD 121, Read-across)                            |  |  |
| Bioaccumulative potential                                     | Low potential for bioaccumulation (BCF < 500).  |  |  |
| ethylbenzene (100-41-4)                                       |   |  |  |
| BCF - Fish [1]  | 1 (6 week(s), Oncorhynchus kisutch, Flow-through system, Salt water, Experimental value)  |  |  |
| Partition coefficient n-octanol/water (Log Pow)               | 3.6 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)                     |  |  |

## Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

| ethylbenzene (100-41-4)                                    |  |  |
|--|--|--|
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 2.71 (log Koc, PCKOCWIN v1.66, QSAR)   |  |
| Bioaccumulative potential                                  | Low potential for bioaccumulation (BCF < 500).   |  |
| methyl acetate (79-20-9)                                   |  |  |
| BCF - Fish [1]   | < 1 (Pisces, Literature study)   |  |
| Partition coefficient n-octanol/water (Log Pow)            | 0.18 (Experimental value, 20 °C)   |  |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP) |  |
| Bioaccumulative potential                                  | Low potential for bioaccumulation (Log Kow < 4).   |  |

## 12.4. Mobility in soil

| RAPTOR CALIPER ENAMEL REAL RED                             |  |  |
|--|--|--|
| Mobility in soil   | No additional information available  |  |
| Xylene (1330-20-7)   |  |  |
| Surface tension  | 28.01 – 29.76 mN/m (25 °C)   |  |
| Partition coefficient n-octanol/water (Log Pow)            | 3.2 (Read-across, 20 °C)   |  |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 2.73 (log Koc, Equivalent or similar to OECD 121, Read-across)   |  |
| Ecology - soil   | Low potential for adsorption in soil. May be harmful to plant growth, blooming and fruit formation.  |  |
| ethylbenzene (100-41-4)                                    |  |  |
| Surface tension  | 71.2 mN/m (23 °C, 0.058 g/l, EU Method A.5: Surface tension)   |  |
| Partition coefficient n-octanol/water (Log Pow)            | 3.6 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)  |  |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 2.71 (log Koc, PCKOCWIN v1.66, QSAR)   |  |
| Ecology - soil   | Low potential for adsorption in soil. Toxic to soil organisms.   |  |
| methyl acetate (79-20-9)                                   |  |  |
| Surface tension  | 24 mN/m (20 °C)  |  |
| Partition coefficient n-octanol/water (Log Pow)            | 0.18 (Experimental value, 20 °C)   |  |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP) |  |
| Ecology - soil   | Highly mobile in soil.   |  |

## 12.5. Other adverse effects

Ozone : Not classified

Other adverse effects : No additional information available

## **SECTION 13: Disposal considerations**

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

8/2/2023 (Issue date) NZ - en 10/13

## Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

## SECTION 14: Transport information

#### 14.1. UN number

 UN-No.(UN RTDG)
 : 1950

 UN-No. (IMDG)
 : 1950

 UN-No. (IATA)
 : 1950

## 14.2. UN Proper Shipping Name

Proper Shipping Name (UN RTDG) : AEROSOLS
Proper Shipping Name (IMDG) : AEROSOLS
Proper Shipping Name (IATA) : Aerosols, flammable

## 14.3. Transport hazard class(es)

#### **UN RTDG**

Transport hazard class(es) (UN RTDG) : 2.1
Danger labels (UN RTDG) : 2.1



#### **IMDG**

Transport hazard class(es) (IMDG) : 2.1
Danger labels (IMDG) : 2.1



## IATA

Transport hazard class(es) (IATA) : 2.1
Danger labels (IATA) : 2.1



## 14.4. Packing group

Packing group (UN RTDG) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

## 14.5. Environmental hazards

Dangerous for the environment : False
Marine pollutant : No

Other information : No supplementary information available

## 14.6. Special precautions for user

#### Transport by road and rail

Special provisions (UN RTDG) : 63, 190, 277, 327, 344, 381

Limited quantities (UN RTDG) : See SP 277

Excepted quantities (UN RTDG) : E0

Packing instruction (UN RTDG) : P207, LP200

Special packing provisions (UN RTDG) : PP87, L2

Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

8/2/2023 (Issue date) NZ - en 11/13

## Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

Packing instructions (IMDG) : P207, LP200 Special packing provisions (IMDG) : PP87, L2

EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES

EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)

Stowage category (IMDG) : None
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

Air transport

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

## 14.7. Transport in bulk according to IMO instruments

Not applicable

## 14.8. Hazchem or Emergency Action Code

Not applicable

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations specific for the product in question

#### **Hazardous Substances and New Organisms Act**

HSNO Approval Number : HSR002517 Group standard : Aerosols

| Group diamatal     | . 710100010 |
|--------------------|-------------|
| Xylene (1330-20-7) |             |

HSNO Approval Number HSR000983

## ethylbenzene (100-41-4)

## Hazardous Substances and New Organisms Act

**Hazardous Substances and New Organisms Act** 

HSNO Approval Number HSR001151

#### methyl acetate (79-20-9)

#### Hazardous Substances and New Organisms Act

HSNO Approval Number HSR001188

## 15.2. Chemical safety assessment

No additional information available

## **SECTION 16: Other information**

Issue date : 8/2/2023

## Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

| Full text of H-statements        |  |  |
|----------------------------------|--|--|
| Acute Tox. 4 (Dermal)            | Acute toxicity (dermal), Category 4  |  |
| Acute Tox. 4 (Inhalation)        | Acute toxicity (inhal.), Category 4  |  |
| Acute Tox. 4 (Inhalation:vapour) | Acute toxicity (inhalation:vapour) Category 4  |  |
| Aerosol 1                        | Aerosol, Category 1  |  |
| Aquatic Acute 2                  | Hazardous to the aquatic environment – Acute Hazard, Category 2                            |  |
| Aquatic Acute 3                  | Hazardous to the aquatic environment – Acute Hazard, Category 3                            |  |
| Aquatic Chronic 3                | Hazardous to the aquatic environment – Chronic Hazard, Category 3                          |  |
| Asp. Tox. 1                      | Aspiration hazard, Category 1  |  |
| Eye Irrit. 2                     | Serious eye damage/eye irritation, Category 2  |  |
| Flam. Liq. 2                     | Flammable liquids, Category 2  |  |
| Flam. Liq. 3                     | Flammable liquids, Category 3  |  |
| Repr. 2                          | Reproductive toxicity, Category 2  |  |
| Skin Irrit. 2                    | Skin corrosion/irritation, Category 2  |  |
| STOT RE 2                        | Specific target organ toxicity – Repeated exposure, Category 2                             |  |
| STOT SE 3                        | Specific target organ toxicity – Single exposure, Category 3, Narcosis                     |  |
| STOT SE 3                        | Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation |  |
| H222                             | Extremely flammable aerosol  |  |
| H225                             | Highly flammable liquid and vapour   |  |
| H226                             | Flammable liquid and vapour  |  |
| H304                             | May be fatal if swallowed and enters airways   |  |
| H312                             | Harmful in contact with skin   |  |
| H315                             | Causes skin irritation   |  |
| H319                             | Causes serious eye irritation  |  |
| H332                             | Harmful if inhaled   |  |
| H335                             | May cause respiratory irritation   |  |
| H336                             | May cause drowsiness or dizziness  |  |
| H361                             | Suspected of damaging fertility or the unborn child  |  |
| H373                             | May cause damage to organs through prolonged or repeated exposure                          |  |
| H401                             | Toxic to aquatic life  |  |
| H402                             | Harmful to aquatic life  |  |
| H412                             | Harmful to aquatic life with long lasting effects  |  |

Safety Data Sheet (SDS), New Zealand

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.