

RAPTOR FLAMEPROOF SATIN CLEAR AEROSOL

Version: 3.0 Date of issue: July 2024

TECHNICAL DATASHEET

A professional quality, flameproof paint, ideal for use on exhaust manifolds, headers, exhaust systems and other surfaces that require protection from very high heat. RAPTOR Flameproof is based on an advanced ceramic technology and high heat resistant pigments that withstand temperatures up to 2000 °F

- Heat resistant intermittently up to 2000 °F
- Superior adhesion
- Good chemical resistance against automotive fluids and common solvents when cured

Product	Order Code	Format	Shelf Life
RAPTOR FLAMEPROOF SATIN CLEAR AEROSOL	UP4941	10oz Aerosol	2 years

APPLICATION INFORMATION



FOR PPE
RECOMMENDATIONS
REFER TO SDS

IMPORTANT: FOR PROFESSIONAL USE ONLY. Read full instructions before use. This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the safety data sheet for full handling instructions and personal protection information.

Surface Preparation



Substrate

- RAPTOR Flameproof paints

Degreaser

- Waterbased degreaser
- Isopropyl Alcohol 70/30

Do not use mineral spirit

Abrasion

- P800-P1000

HOW TO USE:

1. If spraying over previously painted surfaces, clean and degrease. Mask any areas as required.
2. Sand painted surfaces with P800-P1000 sandpaper and reclean using a waterborne degreaser on a wipe.
3. Thoroughly shake can for at least 2 mins before use.
4. Always wear safety goggles and rubber gloves before spraying.
5. Apply 2 coats @ 10inches from surface, waiting 10 mins between coats.
6. To clean – invert can and spray until only propellant sprays.
7. Touch dry in 30 mins at 70°F.
8. Once all coats applied, allow to dry for a minimum of 4 hours (Drying overnight is recommended) to allow the solvents to leave the film and then follow the steps to obtain the full cure:
If on the vehicle, run at idle for at least 30 mins. Let it cool down and run again under normal conditions for at least 30 mins.
If off the vehicle, bake at 300°F for 1 hour.

For optimum properties it is recommended to use RAPTOR Flameproof Satin Clear in conjunction with other RAPTOR Flameproof paints

Mixing



Shake the aerosol can for at least 2 minutes before use. Reshake for 30 seconds between coats.

Application



Application Temperature	70 °F
Distance from the surface	25 cm / 10 inches
Flash-off at 70°F	10 mins
Dust Free at 70°F	30 mins
Number of Coats	2-3

Overcoating



Overcoating window: Up to 12 hours. If allowed to dry longer than 12 hours, abrade with P800 grit, clean with waterbased degreaser then re-apply

NOTE: There is no need to cure between primer, topcoat and clearcoat but it is needed after the full system is applied. If you want to overcoat after curing the coating, abrade with P800 and touch up if substrate is showing through

TECHNICAL INFORMATION

Physical properties



Appearance	aerosol.
Color	Satin Clear

Storage



Aerosol cans should be stored for two hours at room temperature before use. For long term storage, keep in a dry well ventilated area and away from direct sunlight and frost. To clear the nozzle and maximise the lifespan of your aerosol, always invert the can and spray upside down for a few seconds after each use. Should the nozzle become blocked, remove it from the can and soak it in gentle thinners.

Protect from sunlight. Do not expose to temperatures exceeding 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Keep only in original container.

Recommended storage temperature	41 - 77 °F
--	------------

Associated Products



Product	Order Code	Format
RAPTOR FLAMEPROOF GREY PRIMER AEROSOL	UP4940	10oz Aerosol
RAPTOR FLAMEPROOF FLAT BLACK AEROSOL	UP4942	10oz Aerosol
RAPTOR FLAMEPROOF FLAT RED AEROSOL	UP4943	10oz Aerosol

RAPTOR FLAMEPROOF SATIN CLEAR AEROSOL

Version: 3.0 Date of issue: July 2024

TECHNICAL DATASHEET

RAPTOR FLAMEPROOF SATIN CLEAR AEROSOL

UP4941

10oz Aerosol