

SECTION 1: Product identifier

1.1. GHS Product identifier

Product form : Mixture
Trade name : RAPTOR PROTECTIVE COATING BASE
Product code : RLB/200, RLT/200, RLW/200

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coating
Restrictions on use : Consumer uses: Private households (= general public = consumers)

1.4. Details of manufacturer or importer

Supplier

U-POL Australia Pty Limited Ltd

55 Leland Street

Penrith NSW 2750

Australia

T 02 4731 2655 - F 02 4731 2611

info@u-pol.com.au - www.u-pol.com

Supplier

U-POL New Zealand Limited Ltd

c/o Lindsay & Associates Unit H, 12 Amera Place, East Tamaki

Manukau City Auckland 2013

New Zealand

T + 612 4731 2655 / 027 630 3691 - F + 612 4731 2611

info@u-pol.co.nz - www.u-pol.com

1.5. Emergency phone number

Emergency number : Australia (CHEMTREC): + (61) - 290372994 ; New Zealand (National Poisons Centre): 0800 764 766

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable liquids, Category 2	H225
Serious eye damage/eye irritation, Category 2A	H319
Skin sensitisation, Category 1	H317
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Flame

Exclamation
mark

Signal word (GHS AU) :

Danger

Contains

: acetone (10 – 30 %); n-butyl acetate (< 10 %); reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (< 10 %); reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -poly(oxyethylene) (< 10 %)

Hazard statements (GHS AU) :

: H225 - Highly flammable liquid and vapour
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness

RAPTOR PROTECTIVE COATING BASE

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Precautionary statements (GHS AU)	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 - Ground and bond container and receiving equipment. P241 - Use explosion-proof equipment. P261 - Avoid breathing fume, vapours, spray. P264 - Wash hands thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear face protection, protective clothing, protective gloves. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water . P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 - Call a POISON CENTER or doctor if you feel unwell. P321 - Specific treatment (see supplemental first aid instruction on this label). P333+P313 - If skin irritation or rash occurs: Get medical attention. P337+P313 - If eye irritation persists: Get medical attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P370+P378 - In case of fire: Use media other than water to extinguish. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up. P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
-----------------------------------	---

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition and information on ingredients

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
acetone	67-64-1	10 – 30	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Other substances (not contributing to the classification of this product)	-	84.3	-

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Symptoms caused by exposure

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

RAPTOR PROTECTIVE COATING BASE

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

4.3. Medical attention and special treatment

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapour.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

Hazchem Code : * 3YE

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Protective clothing. Gloves. Safety glasses.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapours, spray, fume. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

For containment : Contain released product. Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

Precautions for safe handling

: Keep away from Heat and ignition sources. No smoking.

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing vapours, spray, fume. Avoid contact with skin and eyes.

Hygiene measures

: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

Storage conditions

: Ground/bond container and receiving equipment.

: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

RAPTOR PROTECTIVE COATING BASE

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Storage temperature	: < 25 °C
Storage area	: Store in well ventilated area.
Special rules on packaging	: Keep only in original container.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

acetone (67-64-1)	
Australia - Occupational Exposure Limits	
Local name	Acetone
OES TWA [1]	1185 mg/m ³
OES TWA [2]	500 ppm
OES STEL	2375 mg/m ³
OES STEL [ppm]	1000 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)
New Zealand - Occupational Exposure Limits	
Local name	Acetone
WES-TWA (OEL TWA) [1]	1185 mg/m ³
WES-TWA (OEL TWA) [2]	500 ppm
WES-STEEL (OEL STEL)	2375 mg/m ³
WES-STEEL (OEL STEL) [ppm]	1000 ppm
Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 12th Edition
New Zealand - Biological Exposure Indices	
Local name	Acetone
BEI	50 mg/l Parameter: Acetone - Medium: Urine - Sampling time: End of shift
Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 12th Edition

8.2. Biological Monitoring

No additional information available

8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment	: Gloves. Protective clothing. Safety glasses. Gas mask.
Materials for protective clothing	: Impermeable clothing
Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s)



Environmental exposure controls : Avoid release to the environment.

RAPTOR PROTECTIVE COATING BASE

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

SECTION 9: Physical and chemical properties

Physical state	: Liquid
Appearance	: Viscous. Liquid.
Colour	: Black
Odour	: Acetone odour
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: Melting point: Not applicable
Boiling point	: 56 °C Acetone
Flash point	: -17 °C Acetone
Auto-ignition temperature	: No data available
Flammability	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Density	: Density: 1.125 (1.1 – 1.14) g/cm ³
Solubility	: insoluble in water. soluble in most organic solvents.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 7777.778 mm ² /s
Viscosity, dynamic	: 8750 (7500 – 10000) cP (20°C)
Explosive properties	: No data available
Explosive limits	: No data available
Minimum ignition energy	: No data available
VOC content	: 417 g/l
VOC content - Regulatory	: No data available
Percent Solids	: 62.82 wt%

SECTION 10: Stability and reactivity

Reactivity	: Highly flammable liquid and vapour.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	: No additional information available
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

acetone (67-64-1)	
LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female
LD50 dermal rabbit	> 15800 mg/kg bodyweight (24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4
ATE AU (oral)	5800 mg/kg bodyweight

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

RAPTOR PROTECTIVE COATING BASE

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
RAPTOR PROTECTIVE COATING BASE	
Viscosity, kinematic	7777.778 mm ² /s

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

acetone (67-64-1)	
LC50 - Fish [1]	6210 – 8120 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Measured concentration)
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
BCF - Fish [1]	0.69 (Pisces, Literature study)
Partition coefficient n-octanol/water (Log Pow)	-0.23 (Test data)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

12.2. Persistence and degradability

acetone (67-64-1)	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance
Chemical oxygen demand (COD)	1.92 g O ₂ /g substance
ThOD	2.2 g O ₂ /g substance

12.3. Bioaccumulative potential

acetone (67-64-1)	
BCF - Fish [1]	0.69 (Pisces, Literature study)
Partition coefficient n-octanol/water (Log Pow)	-0.23 (Test data)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

RAPTOR PROTECTIVE COATING BASE

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

12.4. Mobility in soil

acetone (67-64-1)

Surface tension	23.3 mN/m (20 °C)
Partition coefficient n-octanol/water (Log Pow)	-0.23 (Test data)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	See section 12.1 on ecotoxicology 0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

Ozone : Not classified
Other adverse effects : No additional information available

RAPTOR PROTECTIVE COATING BASE

Fluorinated greenhouse gases	False
------------------------------	-------

acetone (67-64-1)

Fluorinated greenhouse gases	False
------------------------------	-------

SECTION 13: Disposal considerations

Regional legislation (waste) : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

14.1. UN number

UN-No. (ADG) : 1263
UN-No. (IMDG) : 1263
UN-No. (IATA) : 1263

14.2. UN Proper Shipping Name

Proper Shipping Name (ADG) : PAINT
Proper Shipping Name (IMDG) : PAINT
Proper Shipping Name (IATA) : Paint

14.3. Transport hazard class(es)

ADG

Transport hazard class(es) (ADG) : 3
Danger labels (ADG) : 3



IMDG

Transport hazard class(es) (IMDG) : 3
Danger labels (IMDG) : 3



RAPTOR PROTECTIVE COATING BASE

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

IATA

Transport hazard class(es) (IATA) : 3
Danger labels (IATA) : 3



14.4. Packing group

Packing group (ADG) : II - Substances presenting medium danger
Packing group (IMDG) : II
Packing group (IATA) : II

14.5. Environmental hazards

Marine pollutant : No
Dangerous for the environment : No
Other information : No supplementary information available

14.6. Special precautions for user

Specific storage requirement : No data available
Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available

Transport by road and rail

UN-No. (ADG) : 1263
Special provision (ADG) : 163, 367
Limited quantities (ADG) : 5I
Packing instructions (ADG) : P001, IBC02
Special packing provisions (ADG) : PP1
Portable tank and bulk container instructions (ADG) : T4
Portable tank and bulk container special provisions (ADG) : TP1, TP8, TP28

Transport by sea

UN-No. (IMDG) : 1263
Special provisions (IMDG) : 163, 367
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP8, TP28
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage) : S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER
Stowage category (IMDG) : B
Properties and observations (IMDG) : Miscibility with water depends upon the composition.

Air transport

UN-No. (IATA) : 1263
PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
Special provisions (IATA) : A3, A72, A192

RAPTOR PROTECTIVE COATING BASE

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

ERG code (IATA) : 3L

14.8. Hazchem or Emergency Action Code

Hazchem Code : * 3YE

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR002662

Group standard : Surface coatings and colourants

acetone (67-64-1)

Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR001070
----------------------	-----------

Xylene (1330-20-7)

Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR000983
----------------------	-----------

15.2. International agreements

No additional information available

SECTION 16: Other information

Revision date : 12/05/2022

Classification

Flam. Liq. 2	H225
--------------	------

Eye Irrit. 2A	H319
---------------	------

Skin Sens. 1	H317
--------------	------

STOT SE 3	H336
-----------	------

Full text of H-statements

Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
---------------	--

Flam. Liq. 2	Flammable liquids, Category 2
--------------	-------------------------------

Skin Sens. 1	Skin sensitisation, Category 1
--------------	--------------------------------

STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
-----------	--

H225	Highly flammable liquid and vapour
------	------------------------------------

H317	May cause an allergic skin reaction
------	-------------------------------------

H319	Causes serious eye irritation
------	-------------------------------

H336	May cause drowsiness or dizziness
------	-----------------------------------

RAPTOR PROTECTIVE COATING BASE

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.