

RAPTOR



RAPTOR 1K PRO TOUCH UP PAINT



DESCRIPTION

A 1K professional Touch Up paint for trucks and other vehicles, ideal for repairing damaged areas. RAPTOR Touch Up Paint gives an exceptionally tough and durable finish with outstanding adhesion. It is 5x tougher* than traditional lacquers, giving the best protection from impact and abrasions. Its clog free nozzle makes it easy to use and it can be applied direct to most prepared metals and plastics. RAPTOR Touch Up Paint is available in a range of universal colours designed to match the most popular truck colours.






FEATURES

- 1K Pro Quality
- 5x Tougher*
- Excellent Adhesion
- Clog Free Nozzle
- Fast Drying

TECHNICAL DATA SHEET

RAPTOR 1K PRO TOUCH UP PAINT

Product preparation - application

	It is strongly recommended to use appropriate personal protection equipment during application to avoid respiratory, skin and eye irritation.	
	<p>Clean and degrease. Mask any areas as required.</p> <p>Sand surface with P180-P220 sandpaper and reclean. If primed, sand with P400-P600 sandpaper & reclean. If sound cured paint, sand surface with P800-P1000 sandpaper and reclean.</p> <p>For plastic parts and difficult to sand areas, prime the surface with RAPTOR Adhesion Promoter.</p> <p>Prime any areas of exposed bare metal using RAPTOR Primer, allow to dry before sanding the surface with P400-P600 grit sandpaper & reclean.</p> <p>Thoroughly shake can for at least 2 mins before use.</p> <p>Always wear safety goggles and gloves before spraying.</p> <p>Use only outdoors or in a well-ventilated area.</p>	
	Ready to use	
	Not applicable	
	2 - 3 coats sprayed 15-25cm away from the object	with intermediate flash-off: 5 min - 10 min at 20°C depending on film build final flash-off: 1 hr at 20°C depending on film build




VOC compliant This product mix is out of scope for VOC directive

TECHNICAL DATA SHEET

RAPTOR 1K PRO TOUCH UP PAINT

Products

RAPTOR® 1K PRO TOUCH UP PAINT
RTCB/AL RAPTOR® 1K PRO TOUCH UP PAINT BLACK
RTCG/AL RAPTOR® 1K PRO TOUCH UP PAINT GREY
RTCR/AL RAPTOR® 1K PRO TOUCH UP PAINT RED
RTCS/AL RAPTOR® 1K PRO TOUCH UP PAINT SILVER
RTCW/AL RAPTOR® 1K PRO TOUCH UP PAINT WHITE

	15 - 25 µm 2 coats
	RAPTOR® 1K PRO TOUCH UP PAINT can be overcoated with itself within 2 hours, without the need for sanding, after this time abrade P1000 and clean thoroughly before recoating. Allow 60 mins (@20°C) for the coating to dry before overcoating with RAPTOR Diamond Clear. If left to dry >8 hrs then scuff before coating with RAPTOR Diamond Clear.
	After use, hold aerosol can upside down and spray briefly to clean nozzle. Do not stick pins into the orifice. If the nozzle becomes blocked, remove from the can and soak in gentle thinners before replacing.

Waste treatment	Dispose of contents and container in accordance with all local, regional, national and international regulations.
-----------------	---

Remarks

- Theoretical coverage 2.7m² per unit, assuming 100% transfer efficiency at the recommended film build.
- Aerosol cans should be stored for 2 hours at room temperature before use. For long term storage keep in a dry well ventilated area and away from direct sunlight and frost. Recommended storage temperature 5 - 25°C, recommended application temperature 20°C

Consult Safety Data Sheet prior to use. Observe the precautionary notices displayed on the container.

All other products referred to in the refinish build up are from our brand product range. System properties will not be valid when the related material is used in combination with any other materials or additives which are not part of our brand product range, unless explicitly indicated otherwise.

For professional use only! The information provided in this documentation has been carefully selected and arranged by us. It is based upon our best knowledge on the subject at the date of issuance. The Information is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check the information with regard to up-to-dateness and suitability for his intended purpose. The intellectual property in this Information, including patents, trademarks and copyrights, is protected. All rights reserved. The relevant Material Safety Data Sheet and Warnings displayed on the product label need to be observed. We may modify and/ or discontinue operation of all or portions of this Information at any time in our sole discretion, without notice and assume no responsibility to update the Information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.