

RECOMMENDED APPLICATION PROCESS GUIDE

Personal Protective Equipment: • Air-fed mask or a respirator suitable for paint application Safety glasses

 Protective gloves • Disposable paint overalls

IF USING RAPTOR 4:1 ANTI-CORROSIVE EPOXY PRIMER:

JP4830



SURFACE PREPARATION Remove all loose and flaky material. Degrease the surface using U-POL System 20 Solvent Based Degreaser (UP2012/ UP2022) or Water Based Degreaser (UP2002) to remove dirt and any surface contaminants. Sand the surface with grit P80 to P180. Degrease again and dry thoroughly.



MIXING RAPTOR EPOXY PRIMER Mix 4:1 by volume 4 parts Raptor Epoxy Primer with 1 part of the included Raptor Epoxy Primer Hardener.

Raptor 4:1 Anti-Corrosive Epoxy Primer is only compatible with the included Raptor 4:1 Anti-Corrosive Epoxy Primer Hardener.

ACTIVATE RAPTOR EPOXY PRIMER

Shake the can for 2 minutes. Remove the

button on the cap. Fit the button onto the pin

in the base of the can. With the cap on, place the can upside down on a firm surface. Push

the button all the way down with the palm of your hand to release the activator into the aerosol. Shake the can for an additional 2



EPOXY PRIMER APPLICATION Use an HVLP Gravity Feed Spray Gun at 30

PSI with a 1.4-1.8mm gun tip. You can also apply with a roller or brush. Apply 2-3 coats allowing 10 minutes flash off between coats.



DRY TIMES Sandable: 30 mins @ 140°F Oven Bake Force Dry* 45 mins @ 125°F 8 hours @ 68°F

Touch dry: 2 hours @ 68°F

Raptor topcoat time: 60 minutes - 7 days * If force drying, sand after cool down and before topcoating with Raptor.



APPLICATION

Test on another panel before application. Apply a minimum of 2 coats at a distance of 1 ft from the surface with 5 minute flash off between coats.

PROCESS TOOLS REGULEREN



DRY TIMES Air dry @ 68°F overnight Sandable: After 24 hours Topcoat time: 30 minutes - 24 hours

Step	Part Number	Description
	UP2002/UP2012/UP2022	Water Based or Solvent Based Degreaser
24	UP4830/UP4831	Raptor 4:1 Anti-Corrosive Epoxy Primer
34	UP0324/UP0326	HVLP Gravity Feed Spray Gun
2 B	UP4842	Raptor 2K Anti-Corrosive Epoxy Primer Aerosol

U-POL Technical Support: 1-800-340-7824 www.raptorcoatings.com

U-POL US, Inc. 108 Commerce Way, Easton, PA 18040. Phone: (610) 746-7081 Fax: (610) 743-8654

AEROSOL

minutes.

DRIVING SURFACE PERFECTION®