



DRIVING SURFACE PERFECTION

# RAPTOR 1K TRUCK BED COATING BLACK AEROSOL

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Issue date: 09-02-2020

Version: 1.0

### SECTION 1: Identification

#### 1.1. Product identifier

Product form : Mixture  
 Trade name : RAPTOR 1K TRUCK BED COATING BLACK AEROSOL  
 Product code : UP8413  
 UP Number : UP8413  
 Product group : aerosol

#### 1.2. Recommended use and restrictions on use

Recommended use : Coating

#### 1.3. Supplier

U-POL Canada Limited  
 P.O. Box P.O. BOX 48600  
 BC V7X 1T2 Vancouver - Canada  
 T 1-800-424-9300  
[technicalsupport@u-pol.com](mailto:technicalsupport@u-pol.com) - [www.u-pol.com](http://www.u-pol.com)

#### 1.4. Emergency telephone number

Emergency number : 1-800-424-9300 (CHEMTREC)

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS CA)

Flammable aerosol Category 1	H222
Gases under pressure Liquefied gas	H280
Serious eye damage/eye irritation Category 2	H319
Skin sensitization, Category 1	H317
Carcinogenicity Category 2	H351
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity (repeated exposure) Category 2	H373

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS CA labeling

Hazard pictograms (GHS CA) :



Signal word (GHS CA) : Danger

Hazard statements (GHS CA) :

- H222 - Extremely flammable aerosol
- H280 - Contains gas under pressure; may explode if heated
- H317 - May cause an allergic skin reaction
- H319 - Causes serious eye irritation
- H336 - May cause drowsiness or dizziness
- H351 - Suspected of causing cancer
- H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS CA) :

- P101 - If medical advice is needed, have product container or label at hand.
- P102 - Keep out of reach of children.
- P201 - Obtain special instructions before use.
- P202 - Do not handle until all safety precautions have been read and understood.
- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 - Do not spray on an open flame or other ignition source.
- P251 - Do not pierce or burn, even after use.
- P260 - Do not breathe vapors, spray, fume.
- P264 - Wash hands thoroughly after handling.
- P271 - Use only outdoors or in a well-ventilated area.

# RAPTOR 1K TRUCK BED COATING BLACK AEROSOL

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

P272 - Contaminated work clothing should not be allowed out of the workplace.  
P280 - Wear protective gloves, protective clothing, eye protection.  
P302+P352 - IF ON SKIN: Wash with plenty of water.  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 - IF exposed or concerned: Get medical advice/attention.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P405 - Store locked up.  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards

### 2.4. Unknown acute toxicity (GHS CA)

3.32% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

1.57% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapors))

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
methyl acetate	methyl acetate acetate of methyl / acetic acid methyl ester / acetic acid, methyl ester / devoton / ethyl ester of monoacetyl acid / methyl acetate / methyl acetate, anhydrous / methyl acetic ester / methyl ester acetic acid / methyl ethanoate / tereton	(CAS-No.) 79-20-9	15 – 30	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
n-butyl acetate	n-butyl acetate 1-acetoxybutane / 1-butyl acetate / acetate of butyl / acetic acid n-butyl ester / acetic acid normal-butyl ester / acetic acid, butyl ester / BUAC / BuAc (=butyl acetate) / butanolacetate / butyl acetate / butyl ethanoate / n-BuAc / n-butyl acetate / normal-butylacetate / normal-butylethanoate	(CAS-No.) 123-86-4	13 – 15	Flam. Liq. 3, H226 STOT SE 3, H336
acetone	2-propanon / 2-propanone / acetone / acetone NF / acetone oil / AI3-01238 / Caswell No.004 / chevron acetone / dimethyl formaldehyde / dimethyl ketone / dimethylketal / Dimethylketon / DMK (=dimethyl ketone) / FEMA No 3326 / ketone propane / KTI acetone / methyl acetyl / methylketon / propan-2-one / propanone / pyroacetic acid / pyroacetic ether / pyroacetic spirit / STEC 4908105	(CAS-No.) 67-64-1	10 – 13	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Xylene	AMSCO / benzene, dimethyl- / byk 310 / dimethylbenzene, mixture of isomers / dimethylbenzol, mixture of isomers / formula No 00651 / mebon thinner type 2 / methyltoluene, mixture of isomers / mixed xylenes / paint / solvent xylene / violet 3 / xylene / xylene, mixed isomers, pure / xylol / xylol, mixture of isomers	(CAS-No.) 1330-20-7	3 – 5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304

# RAPTOR 1K TRUCK BED COATING BLACK AEROSOL

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
carbon black	10 B / 200303 / 3500 B / 40 B / acetylen black / acetylene black / acticarbon AC 35 / AD 200 / AD 200(carbon) / AM black / amorphous carbon / aquafine AF black E 2B / aquafine black E ZB / aro / aroflow / arogen / aromex / arotone / arovel / arrow / asahi 35 / asahi 60 / asahi 70 / asahi 80 / asahithermal / ASM(carbon) / ATG 60 / ATG 70 / atlantic / ATR 077 / austin black / austin black 325 / AX 3023 / BK 6 / BK 6(carbon black) / black FW / black pearls / black pearls 1000 / black pearls 1000A80 / black pearls 1100 / black pearls 1300 / black pearls 2000 / black pearls 700 / black pearls 800 / black pearls 880 / black pearls 900 / black pearls 1 / C.I. 77266 / C.I. pigment black 6 / C.I. pigment black 7 / cabot 330 / cabot 607 / calblack N 220 / cancarb / carbalac 2 / carbodis / carbodis 100 / carbodis 80 / carbolac / carbolac 1 / carbomet / CARBON BLACK / carbon black BV and V / carbon black corax N330 / carbon black EB501 / carbon black monarch 81 / carbon black pearls / carbon black pigment / carbon black, acetylene / carbon black, channel / carbon black, furnace / carbon black, lamp / carbon black, thermal / carbon, amorphous / CC 40-220 / CD-7037 / channel black / charcoal black / chesacarb / chesacarb E / chesacarb EC / chesacarb K 2 / chezasorb / CK3 / CK4 / CK4(carbon black) / clagon RBDA / collocarb / colour black FW 1 / columbia carbon / CONDUCTEX / CONDUCTEX 40-220 / CONDUCTEX 7055 / CONDUCTEX 900 / CONDUCTEX 950 / CONDUCTEX 975 / CONDUCTEX CC 40-220 / CONDUCTEX N 472 / CONDUCTEX SC / continental(=carbon black) / continex / CONTINEX N 330 / CONTINEX N 356 / corac P / corax / corax 234 / corax 3HS CSX 147 / corax A / corax L / corax L 29 / corax L 6 / corax N220 / corax N539 / corax N650 / corax N683 / corax N765 / corax P / croflex / crolac / CSX 150A / CSX 150A2 / CSX 174 / CSX 200A / CSX 99 / CSX191 / CSX230 / CSX242 / DEGUSSA black FW / DEGUSSA(=carbon black) / dermmapol black G / DG 100 / diablack 2350 / diablack 3500B / diablack 52 / diablack A / diablack E / diablack G / diablack H / diablack MA 100 / diablack MA 8 / diablack MA 8B / diablack SH / disperse black SD 9020 / dixie(=carbon black) / dixiecell / dixiedensed / dixitherm / DMG 105a durex O / durex O beads / durex(carbon black) / E carbon black / eagle germantown / EDO / EDO(carbon black) / eldic EC 8013 / ELF / ELF 78 / elfex 475 / ELF-O / elftex / elftex 115 / elftex 12 / elftex 120 / elftex 125 / elftex 150 / elftex 160 / elftex 180 / elftex 280 / elftex 285 / elftex 415 / elftex 430 / elftex 435 / elftex 460 / elftex 465 / elftex 470 / elftex 475 / elftex 480 / elftex 485 / elftex 490 / elftex 495 / elftex 5 / elftex 570 / elftex 670 / elftex 675 / elftex 8 / elftex TP / elftex-E280 / emacol NS black 4901 / EPC / EPC(carbon black) / essex / excelsior / EXP / EXP 1 / EXP 2 / EXP(carbon black) / explosion / explosion acetylene black / explosion black / F 122 / farbruss / farbruss FW 1 / farbruss S 160 (Farbruss) black / flamruss / furnace black / furnal / furnal 500 / furnex / furnex N 765 / FW 200 / FW 200(carbon) / G 2 / G2(carbon black) / gas black / gas-furnace black / gastex /	(CAS-No.) 1333-86-4	1 – 1.5	Carc. 2, H351
07-27-2021				3/22



# RAPTOR 1K TRUCK BED COATING BLACK AEROSOL

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### 5.4. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

### 6.2. Methods and materials for containment and cleaning up

Methods for cleaning up : Mechanically recover the product. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe vapors, spray, fume. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Keep container tightly closed. Keep cool.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

n-butyl acetate (123-86-4)		
Canada (Quebec)	VECD (OEL STEL) [ppm]	150 ppm
Canada (Quebec)	VEMP (OEL TWA) [ppm]	50 ppm
Canada (Quebec)	Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Alberta	OEL STEL	950 mg/m <sup>3</sup>
Alberta	OEL STEL [ppm]	200 ppm
Alberta	OEL TWA	713 mg/m <sup>3</sup>
Alberta	OEL TWA [ppm]	150 ppm
Alberta	Notations and remarks	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required.
Alberta	Regulatory reference	Alberta Regulation 87/2009 (Alberta Regulation 150/2020)
British Columbia	OEL STEL [ppm]	150 ppm
British Columbia	OEL TWA [ppm]	50 ppm
British Columbia	Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Manitoba	OEL STEL [ppm]	150 ppm
Manitoba	OEL TWA [ppm]	50 ppm
Manitoba	Notations and remarks	TLV® Basis: Eye & URT irr
Manitoba	Regulatory reference	ACGIH
Newfoundland & Labrador	OEL STEL [ppm]	150 ppm
Newfoundland & Labrador	OEL TWA [ppm]	50 ppm
Newfoundland & Labrador	Notations and remarks	TLV® Basis: Eye & URT irr
Newfoundland & Labrador	Regulatory reference	ACGIH
Nova Scotia	OEL STEL [ppm]	150 ppm
Nova Scotia	OEL TWA [ppm]	50 ppm

# RAPTOR 1K TRUCK BED COATING BLACK AEROSOL

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

<b>n-butyl acetate (123-86-4)</b>		
Nova Scotia	Notations and remarks	TLV® Basis: Eye & URT irr
Nova Scotia	Regulatory reference	ACGIH
Nunavut	OEL STEL [ppm]	200 ppm
Nunavut	OEL TWA [ppm]	150 ppm
Nunavut	Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016
Northwest Territories	OEL STEL [ppm]	200 ppm
Northwest Territories	OEL TWA [ppm]	150 ppm
Northwest Territories	Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Ontario	OEL STEL [ppm]	200 ppm
Ontario	OEL TWA [ppm]	150 ppm
Ontario	Regulatory reference	Ontario Occuational Exposure Limits under Regulation 833
Prince Edward Island	OEL STEL [ppm]	150 ppm
Prince Edward Island	OEL TWA [ppm]	50 ppm
Prince Edward Island	Notations and remarks	TLV® Basis: Eye & URT irr
Prince Edward Island	Regulatory reference	ACGIH
Saskatchewan	OEL STEL [ppm]	200 ppm
Saskatchewan	OEL TWA [ppm]	150 ppm
Saskatchewan	Regulatory reference	The Occupational Health and Safety Regulations, 1996. Chapter O-1.1 Reg 1
<b>acetone (67-64-1)</b>		
Canada (Quebec)	VECD (OEL STEL)	2380 mg/m <sup>3</sup>
Canada (Quebec)	VECD (OEL STEL) [ppm]	1000 ppm
Canada (Quebec)	VEMP (OEL TWA)	1190 mg/m <sup>3</sup>
Canada (Quebec)	VEMP (OEL TWA) [ppm]	500 ppm
Canada (Quebec)	Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Alberta	OEL STEL	1800 mg/m <sup>3</sup>
Alberta	OEL STEL [ppm]	750 ppm
Alberta	OEL TWA	1200 mg/m <sup>3</sup>
Alberta	OEL TWA [ppm]	500 ppm
Alberta	Regulatory reference	Alberta Regulation 87/2009 (Alberta Regulation 150/2020)
British Columbia	OEL STEL [ppm]	500 ppm
British Columbia	OEL TWA [ppm]	250 ppm
British Columbia	Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Manitoba	OEL STEL [ppm]	500 ppm
Manitoba	OEL TWA [ppm]	250 ppm
Manitoba	Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Manitoba	Regulatory reference	ACGIH
New Brunswick	OEL STEL [ppm]	500 ppm
New Brunswick	OEL TWA [ppm]	250 ppm
New Brunswick	Notations and remarks	eye irr; CNS impair; BEI
Newfoundland & Labrador	OEL STEL [ppm]	500 ppm
Newfoundland & Labrador	OEL TWA [ppm]	250 ppm
Newfoundland & Labrador	Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Newfoundland & Labrador	Regulatory reference	ACGIH
Nova Scotia	OEL STEL [ppm]	500 ppm
Nova Scotia	OEL TWA [ppm]	250 ppm

# RAPTOR 1K TRUCK BED COATING BLACK AEROSOL

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

<b>acetone (67-64-1)</b>		
Nova Scotia	Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Nova Scotia	Regulatory reference	ACGIH
Nunavut	OEL STEL [ppm]	750 ppm
Nunavut	OEL TWA [ppm]	500 ppm
Nunavut	Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016
Northwest Territories	OEL STEL [ppm]	750 ppm
Northwest Territories	OEL TWA [ppm]	500 ppm
Northwest Territories	Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Ontario	OEL STEL [ppm]	500 ppm
Ontario	OEL TWA [ppm]	250 ppm
Ontario	Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
Prince Edward Island	OEL STEL [ppm]	500 ppm
Prince Edward Island	OEL TWA [ppm]	250 ppm
Prince Edward Island	Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Prince Edward Island	Regulatory reference	ACGIH
Saskatchewan	OEL STEL [ppm]	750 ppm
Saskatchewan	OEL TWA [ppm]	500 ppm
Saskatchewan	Regulatory reference	The Occupational Health and Safety Regulations, 1996. Chapter O-1.1 Reg 1
<b>quartz (14808-60-7)</b>		
Canada (Quebec)	VEMP (OEL TWA)	0.1 mg/m³ Rd
Canada (Quebec)	Notations and remarks	C2, EM
Canada (Quebec)	Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Alberta	OEL TWA	0.025 mg/m³
Alberta	Notations and remarks	Carcinogenicity A2
Alberta	Regulatory reference	Alberta Regulation 87/2009 (Alberta Regulation 150/2020)
British Columbia	OEL TWA	0.025 mg/m³ Respirable
British Columbia	Notations and remarks	ACGIH Carcinogenicity category A2; IARC group 1 carcinogen
British Columbia	Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Manitoba	OEL TWA	0.025 mg/m³ (R - Respirable particulate matter)
Manitoba	Notations and remarks	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Manitoba	Regulatory reference	ACGIH
Newfoundland & Labrador	OEL TWA	0.025 mg/m³ (R - Respirable particulate matter)
Newfoundland & Labrador	Notations and remarks	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Newfoundland & Labrador	Regulatory reference	ACGIH
Nova Scotia	OEL TWA	0.025 mg/m³ (R - Respirable particulate matter)
Nova Scotia	Notations and remarks	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Nova Scotia	Regulatory reference	ACGIH
Nunavut	OEL TWA	0.05 mg/m³ (respirable fraction)
Nunavut	Notations and remarks	Designated substance
Nunavut	Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016
Northwest Territories	OEL TWA	0.05 mg/m³ (respirable fraction)
Northwest Territories	Notations and remarks	Designated substance

# RAPTOR 1K TRUCK BED COATING BLACK AEROSOL

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

<b>quartz (14808-60-7)</b>		
Northwest Territories	Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Ontario	OEL TWA	0.1 mg/m <sup>3</sup> (R - Respirable fraction)
Ontario	Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
Prince Edward Island	OEL TWA	0.025 mg/m <sup>3</sup> (R - Respirable particulate matter)
Prince Edward Island	Notations and remarks	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Prince Edward Island	Regulatory reference	ACGIH
Saskatchewan	OEL TWA	0.05 mg/m <sup>3</sup> (respirable fraction)
Saskatchewan	Notations and remarks	Designated Chemical Substance
Saskatchewan	Regulatory reference	The Occupational Health and Safety Regulations, 1996. Chapter O-1.1 Reg 1
<b>carbon black (1333-86-4)</b>		
Canada (Quebec)	VEMP (OEL TWA)	3 mg/m <sup>3</sup> Id
Canada (Quebec)	Notations and remarks	C3
Canada (Quebec)	Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Alberta	OEL TWA	3.5 mg/m <sup>3</sup>
Alberta	Regulatory reference	Alberta Regulation 87/2009 (Alberta Regulation 150/2020)
British Columbia	OEL TWA	3 mg/m <sup>3</sup> Inhalable
British Columbia	Notations and remarks	IARC group 2B carcinogen
British Columbia	Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Manitoba	OEL TWA	3 mg/m <sup>3</sup> (I - Inhalable particulate matter)
Manitoba	Notations and remarks	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Manitoba	Regulatory reference	ACGIH
New Brunswick	OEL TWA	3 mg/m <sup>3</sup>
New Brunswick	Notations and remarks	Bronchitis
Newfoundland & Labrador	OEL TWA	3 mg/m <sup>3</sup> (I - Inhalable particulate matter)
Newfoundland & Labrador	Notations and remarks	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Newfoundland & Labrador	Regulatory reference	ACGIH
Nova Scotia	OEL TWA	3 mg/m <sup>3</sup> (I - Inhalable particulate matter)
Nova Scotia	Notations and remarks	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Nova Scotia	Regulatory reference	ACGIH
Nunavut	OEL STEL	7 mg/m <sup>3</sup>
Nunavut	OEL TWA	3 mg/m <sup>3</sup>
Nunavut	Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016
Northwest Territories	OEL STEL	7 mg/m <sup>3</sup>
Northwest Territories	OEL TWA	3.5 mg/m <sup>3</sup>
Northwest Territories	Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Ontario	OEL TWA	3 mg/m <sup>3</sup> (I - Inhalable fraction)
Ontario	Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
Prince Edward Island	OEL TWA	3 mg/m <sup>3</sup> (I - Inhalable particulate matter)
Prince Edward Island	Notations and remarks	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)



# RAPTOR 1K TRUCK BED COATING BLACK AEROSOL

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

<b>carbon black (1333-86-4)</b>		
Prince Edward Island	Regulatory reference	ACGIH
Saskatchewan	OEL STEL	7 mg/m <sup>3</sup>
Saskatchewan	OEL TWA	3.5 mg/m <sup>3</sup>
Saskatchewan	Regulatory reference	The Occupational Health and Safety Regulations, 1996. Chapter O-1.1 Reg 1
<b>methyl acetate (79-20-9)</b>		
Canada (Quebec)	VECD (OEL STEL)	757 mg/m <sup>3</sup>
Canada (Quebec)	VECD (OEL STEL) [ppm]	250 ppm
Canada (Quebec)	VEMP (OEL TWA)	606 mg/m <sup>3</sup>
Canada (Quebec)	VEMP (OEL TWA) [ppm]	200 ppm
Canada (Quebec)	Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Alberta	OEL STEL	757 mg/m <sup>3</sup>
Alberta	OEL STEL [ppm]	250 ppm
Alberta	OEL TWA	606 mg/m <sup>3</sup>
Alberta	OEL TWA [ppm]	200 ppm
Alberta	Regulatory reference	Alberta Regulation 87/2009 (Alberta Regulation 150/2020)
British Columbia	OEL STEL [ppm]	250 ppm
British Columbia	OEL TWA [ppm]	200 ppm
British Columbia	Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Manitoba	OEL STEL [ppm]	250 ppm
Manitoba	OEL TWA [ppm]	200 ppm
Manitoba	Notations and remarks	TLV® Basis: Headache; dizziness; nausea; eye dam (degeneration of ganglion cells in the retina)
Manitoba	Regulatory reference	ACGIH
New Brunswick	OEL STEL [ppm]	250 ppm
New Brunswick	OEL TWA [ppm]	200 ppm
New Brunswick	Notations and remarks	eye & URT irr
Newfoundland & Labrador	OEL STEL [ppm]	250 ppm
Newfoundland & Labrador	OEL TWA [ppm]	200 ppm
Newfoundland & Labrador	Notations and remarks	TLV® Basis: Headache; dizziness; nausea; eye dam (degeneration of ganglion cells in the retina)
Newfoundland & Labrador	Regulatory reference	ACGIH
Nova Scotia	OEL STEL [ppm]	250 ppm
Nova Scotia	OEL TWA [ppm]	200 ppm
Nova Scotia	Notations and remarks	TLV® Basis: Headache; dizziness; nausea; eye dam (degeneration of ganglion cells in the retina)
Nova Scotia	Regulatory reference	ACGIH
Nunavut	OEL STEL [ppm]	250 ppm
Nunavut	OEL TWA [ppm]	200 ppm
Nunavut	Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016
Northwest Territories	OEL STEL [ppm]	250 ppm
Northwest Territories	OEL TWA [ppm]	200 ppm
Northwest Territories	Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Ontario	OEL STEL [ppm]	250 ppm
Ontario	OEL TWA [ppm]	200 ppm
Ontario	Regulatory reference	Ontario Occuational Exposure Limits under Regulation 833
Prince Edward Island	OEL STEL [ppm]	250 ppm
Prince Edward Island	OEL TWA [ppm]	200 ppm

# RAPTOR 1K TRUCK BED COATING BLACK AEROSOL

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

<b>methyl acetate (79-20-9)</b>		
Prince Edward Island	Notations and remarks	TLV® Basis: Headache; dizziness; nausea; eye dam (degeneration of ganglion cells in the retina)
Prince Edward Island	Regulatory reference	ACGIH
Saskatchewan	OEL STEL [ppm]	250 ppm
Saskatchewan	OEL TWA [ppm]	200 ppm
Saskatchewan	Regulatory reference	The Occupational Health and Safety Regulations, 1996. Chapter O-1.1 Reg 1
<b>LPG, liquefied, under pressure (68476-85-7)</b>		
Canada (Quebec)	VEMP (OEL TWA)	1800 mg/m <sup>3</sup>
Canada (Quebec)	VEMP (OEL TWA) [ppm]	1000 ppm
Canada (Quebec)	Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Alberta	OEL STEL [ppm]	1500 ppm
Alberta	OEL TWA [ppm]	1000 ppm
Alberta	Regulatory reference	Alberta Regulation 87/2009 (Alberta Regulation 150/2020)
British Columbia	Notations and remarks	Simple asphyxiant; EX (Substance is a flammable asphyxiant or excursions above the exposure limit could approach 10% of the lower explosive limit)
British Columbia	Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Manitoba	Notations and remarks	TLV® Basis: Simple Asphyxiant
Manitoba	Regulatory reference	ACGIH
Newfoundland & Labrador	Notations and remarks	TLV® Basis: Simple Asphyxiant
Newfoundland & Labrador	Regulatory reference	ACGIH
Nova Scotia	Notations and remarks	TLV® Basis: Simple Asphyxiant
Nova Scotia	Regulatory reference	ACGIH
Nunavut	OEL STEL [ppm]	1250 ppm
Nunavut	OEL TWA [ppm]	1000 ppm
Nunavut	Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016
Northwest Territories	OEL STEL [ppm]	1250 ppm
Northwest Territories	OEL TWA [ppm]	1000 ppm
Northwest Territories	Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Ontario	Notations and remarks	See Appendix F: Minimal Oxygen Content
Ontario	Regulatory reference	Ontario Occuational Exposure Limits under Regulation 833
Prince Edward Island	Notations and remarks	TLV® Basis: Simple Asphyxiant
Prince Edward Island	Regulatory reference	ACGIH
Saskatchewan	OEL STEL [ppm]	1250 ppm
Saskatchewan	OEL TWA [ppm]	1000 ppm
Saskatchewan	Regulatory reference	The Occupational Health and Safety Regulations, 1996. Chapter O-1.1 Reg 1
<b>Xylene (1330-20-7)</b>		
Canada (Quebec)	VECD (OEL STEL)	651 mg/m <sup>3</sup>
Canada (Quebec)	VECD (OEL STEL) [ppm]	150 ppm
Canada (Quebec)	VEMP (OEL TWA)	434 mg/m <sup>3</sup>
Canada (Quebec)	VEMP (OEL TWA) [ppm]	100 ppm
Canada (Quebec)	Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Alberta	OEL STEL	651 mg/m <sup>3</sup>
Alberta	OEL STEL [ppm]	150 ppm
Alberta	OEL TWA	434 mg/m <sup>3</sup>
Alberta	OEL TWA [ppm]	100 ppm
Alberta	Regulatory reference	Alberta Regulation 87/2009 (Alberta Regulation 150/2020)

# RAPTOR 1K TRUCK BED COATING BLACK AEROSOL

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

<b>Xylene (1330-20-7)</b>		
British Columbia	OEL STEL [ppm]	150 ppm
British Columbia	OEL TWA [ppm]	100 ppm
British Columbia	Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Manitoba	OEL STEL [ppm]	150 ppm
Manitoba	OEL TWA [ppm]	100 ppm
Manitoba	Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Manitoba	Regulatory reference	ACGIH
New Brunswick	OEL STEL [ppm]	150 ppm
New Brunswick	OEL TWA [ppm]	100 ppm
New Brunswick	Notations and remarks	URT & eye irr; CNS impair
Newfoundland & Labrador	OEL STEL [ppm]	150 ppm
Newfoundland & Labrador	OEL TWA [ppm]	100 ppm
Newfoundland & Labrador	Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Newfoundland & Labrador	Regulatory reference	ACGIH
Nova Scotia	OEL STEL [ppm]	150 ppm
Nova Scotia	OEL TWA [ppm]	100 ppm
Nova Scotia	Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Nova Scotia	Regulatory reference	ACGIH
Nunavut	OEL STEL [ppm]	150 ppm
Nunavut	OEL TWA [ppm]	100 ppm
Nunavut	Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016
Northwest Territories	OEL STEL [ppm]	150 ppm
Northwest Territories	OEL TWA [ppm]	100 ppm
Northwest Territories	Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Ontario	OEL STEL [ppm]	150 ppm
Ontario	OEL TWA [ppm]	100 ppm
Ontario	Regulatory reference	Ontario Occuational Exposure Limits under Regulation 833
Prince Edward Island	OEL STEL [ppm]	150 ppm
Prince Edward Island	OEL TWA [ppm]	100 ppm
Prince Edward Island	Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Prince Edward Island	Regulatory reference	ACGIH
Saskatchewan	OEL STEL [ppm]	150 ppm
Saskatchewan	OEL TWA [ppm]	100 ppm
Saskatchewan	Regulatory reference	The Occupational Health and Safety Regulations, 1996. Chapter O-1.1 Reg 1
<b>ethylbenzene (100-41-4)</b>		
Canada (Quebec)	VEMP (OEL TWA) [ppm]	20 ppm
Canada (Quebec)	Notations and remarks	C3
Canada (Quebec)	Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Alberta	OEL STEL	543 mg/m <sup>3</sup>
Alberta	OEL STEL [ppm]	125 ppm
Alberta	OEL TWA	434 mg/m <sup>3</sup>
Alberta	OEL TWA [ppm]	100 ppm
Alberta	Regulatory reference	Alberta Regulation 87/2009 (Alberta Regulation 150/2020)

# RAPTOR 1K TRUCK BED COATING BLACK AEROSOL

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

<b>ethylbenzene (100-41-4)</b>		
British Columbia	OEL TWA [ppm]	20 ppm
British Columbia	Notations and remarks	IARC group 2B carcinogen
British Columbia	Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Manitoba	OEL TWA [ppm]	20 ppm
Manitoba	Notations and remarks	TLV® Basis: URT irr; kidney dam (nephropathy); cochlear impair. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Manitoba	Regulatory reference	ACGIH
Newfoundland & Labrador	OEL TWA [ppm]	20 ppm
Newfoundland & Labrador	Notations and remarks	TLV® Basis: URT irr; kidney dam (nephropathy); cochlear impair. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Newfoundland & Labrador	Regulatory reference	ACGIH
Nova Scotia	OEL TWA [ppm]	20 ppm
Nova Scotia	Notations and remarks	TLV® Basis: URT irr; kidney dam (nephropathy); cochlear impair. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Nova Scotia	Regulatory reference	ACGIH
Nunavut	OEL STEL [ppm]	125 ppm
Nunavut	OEL TWA [ppm]	100 ppm
Nunavut	Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016
Northwest Territories	OEL STEL [ppm]	125 ppm
Northwest Territories	OEL TWA [ppm]	100 ppm
Northwest Territories	Notations and remarks	Designated substance
Northwest Territories	Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Ontario	OEL TWA [ppm]	20 ppm
Ontario	Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
Prince Edward Island	OEL TWA [ppm]	20 ppm
Prince Edward Island	Notations and remarks	TLV® Basis: URT irr; kidney dam (nephropathy); cochlear impair. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Prince Edward Island	Regulatory reference	ACGIH
Saskatchewan	OEL STEL [ppm]	125 ppm
Saskatchewan	OEL TWA [ppm]	100 ppm
Saskatchewan	Notations and remarks	Designated Chemical Substance
Saskatchewan	Regulatory reference	The Occupational Health and Safety Regulations, 1996. Chapter O-1.1 Reg 1
<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>		
British Columbia	OEL STEL [ppm]	75 ppm
British Columbia	OEL TWA [ppm]	50 ppm
British Columbia	Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Ontario	OEL TWA	270 mg/m³
Ontario	OEL TWA [ppm]	50 ppm
Ontario	Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
<b>2-methoxypropyl acetate (70657-70-4)</b>		
British Columbia	OEL STEL [ppm]	40 ppm
British Columbia	OEL TWA [ppm]	20 ppm
British Columbia	Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)

# RAPTOR 1K TRUCK BED COATING BLACK AEROSOL

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Protective gloves

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: aerosol.
Color	: Black
Odor	: aromatic
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: < 0 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol
Vapor pressure	: No data available
Vapor pressure at 50 °C	: No data available
Relative density	: No data available
Density	: 0.96 g/cm <sup>3</sup>
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Explosion limits	: No data available

### 9.2. Other information

Gas group	: Press. Gas (Liq.)
As Packaged Regulatory VOC	: 545 g/l (4.5 lbs/gal)
As Packaged Actual VOC	: 496 g/l (4.1 lbs/gal)
As Applied Regulatory VOC	: 545 g/l (4.5 lbs/gal)
As Applied Actual VOC	: 496 g/l (4.1 lbs/gal)
Water Content	0 wt%
Exempt Compounds by volume	: 8.9 vol %
Exempt Compounds by weight	: 10.0 wt%
Volatiles	: 69.7 wt%
% EPA HAPS	: 4.1 wt%

# RAPTOR 1K TRUCK BED COATING BLACK AEROSOL

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Percent Solids	: 30.29 wt%
Percent Solids	: 18.88 vol %

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Reactivity	: Extremely flammable aerosol.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Unknown acute toxicity (GHS CA)	3.32% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal) 1.57% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapors))
---------------------------------	---

<b>n-butyl acetate (123-86-4)</b>	
LD50 oral rat	10760 – 12789 mg/kg body weight (Equivalent or similar to OECD 423, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 14112 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	23.4 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Inhalation (mixture of vapour and aerosol), 14 day(s))
LC50 Inhalation - Rat [ppm]	390 ppm/4h
LC50 Inhalation - Rat (Vapours)	> 21 mg/l/4h (4 h, OECD Test Guideline 403, rat, vapours)
ATE CA (oral)	10760 mg/kg body weight
ATE CA (Dermal)	14112 mg/kg body weight
ATE CA (Gases (except aerosol dispensers and lighters))	390 ppmV/4h

<b>acetone (67-64-1)</b>	
LD50 oral rat	5800 mg/kg body weight Animal: rat, Animal sex: female
LD50 dermal rabbit	> 15800 mg/kg body weight (24 h, Rabbit, Male, Weight of evidence, Dermal, 14 day(s))
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4
ATE CA (oral)	5800 mg/kg body weight
ATE CA (Dermal)	20000 mg/kg body weight

<b>carbon black (1333-86-4)</b>	
LD50 oral rat	> 8000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LC50 Inhalation - Rat	> 4.6 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Experimental value, Inhalation (dust))

<b>methyl acetate (79-20-9)</b>	
LD50 oral rat	6482 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	49 mg/l
ATE CA (oral)	6482 mg/kg body weight
ATE CA (vapors)	49 mg/l/4h
ATE CA (dust,mist)	49 mg/l/4h

<b>reaction mass of <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-hydroxypoly(oxyethylene) and <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)</b>	
LD50 oral rat	> 5000 mg/kg (OECD Guideline No. 401 (equivalent to Annex V), limit test, rat, male/female)
LD50 dermal rat	> 2000 mg/kg (OECD Guideline No. 402 (equivalent to Annex V), limit test, rat, male/female)
LC50 Inhalation - Rat	5800 mg/l (OECD Guideline 403, 14d, rat)
ATE CA (vapors)	5800 mg/l/4h
ATE CA (dust,mist)	5800 mg/l/4h

# RAPTOR 1K TRUCK BED COATING BLACK AEROSOL

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

<b>reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)</b>	
LD50 oral rat	3230 mg/kg (OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), rat, male/female)
LD50 dermal rat	> 3170 mg/kg (OECD Guideline 402 (Acute Dermal Toxicity), read-across,
ATE CA (oral)	3230 mg/kg body weight

<b>Xylene (1330-20-7)</b>	
LD50 oral rat	3523 mg/kg body weight (Equivalent or similar to EU Method B.1: Acute Toxicity (Oral), Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	12126 mg/kg (Non-GLP, read-across from supporting substance, single dermal dose under occlusion followed by observation for 14 days)
LD50 dermal rabbit	12126 mg/kg body weight Animal: rabbit, Animal sex: male
LC50 Inhalation - Rat [ppm]	6700 ppm/4h (EU Method B.2 (Acute Toxicity (Inhalation)), 4h, rat, male)
ATE CA (oral)	3523 mg/kg body weight
ATE CA (Dermal)	1100 mg/kg body weight
ATE CA (Gases (except aerosol dispensers and lighters))	6700 ppmV/4h
ATE CA (vapors)	11 mg/l/4h
ATE CA (dust,mist)	1.5 mg/l/4h

<b>ethylbenzene (100-41-4)</b>	
LD50 oral rat	3500 mg/kg (Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	15432 mg/kg body weight (24 h, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat	17.8 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours))
ATE CA (Gases (except aerosol dispensers and lighters))	4500 ppmV/4h
ATE CA (vapors)	11 mg/l/4h
ATE CA (dust,mist)	1.5 mg/l/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
Reproductive toxicity	: Not classified

<b>acetone (67-64-1)</b>	
LOAEL (animal/female, F0/P)	11298 mg/kg body weight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg body weight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)

STOT-single exposure : May cause drowsiness or dizziness.

<b>n-butyl acetate (123-86-4)</b>	
STOT-single exposure	May cause drowsiness or dizziness.

<b>acetone (67-64-1)</b>	
STOT-single exposure	May cause drowsiness or dizziness.

<b>methyl acetate (79-20-9)</b>	
STOT-single exposure	May cause drowsiness or dizziness.

<b>Xylene (1330-20-7)</b>	
STOT-single exposure	May cause respiratory irritation.

: May cause damage to organs through prolonged or repeated exposure.

STOT-repeated exposure

<b>methyl acetate (79-20-9)</b>	
LOAEC (inhalation,rat,vapor,90 days)	2000 mg/l
NOAEC (inhalation,rat,vapor,90 days)	1057 mg/m <sup>3</sup>

# RAPTOR 1K TRUCK BED COATING BLACK AEROSOL

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

<b>Xylene (1330-20-7)</b>	
LOAEL (oral, rat, 90 days)	150 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

<b>ethylbenzene (100-41-4)</b>	
NOAEL (oral, rat, 90 days)	75 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

<b>RAPTOR 1K TRUCK BED COATING BLACK AEROSOL</b>	
Vaporizer	aerosol

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : May cause an allergic skin reaction.

Symptoms/effects after eye contact : Eye irritation.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

<b>n-butyl acetate (123-86-4)</b>	
LC50 - Fish [1]	18 mg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	62 mg/l (Leuciscus idus, static system)
EC50 - Crustacea [1]	44 mg/l Test organisms (species): Daphnia sp.
ErC50 algae	397 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Read-across, GLP)
NOEC (chronic)	23 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic crustacea	23 mg/l
Partition coefficient n-octanol/water (Log Pow)	2.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.268 – 1.844 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

<b>acetone (67-64-1)</b>	
LC50 - Fish [1]	6210 – 8120 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Measured concentration)
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Partition coefficient n-octanol/water (Log Pow)	-0.23 (Test data)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

<b>carbon black (1333-86-4)</b>	
LC50 - Fish [1]	> 1000 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	> 5600 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 24 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	> 10000 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 72h - Algae [1]	> 10000 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

<b>methyl acetate (79-20-9)</b>	
LC50 - Fish [1]	250 – 350 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	1026.7 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 120 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
BCF - Fish [1]	< 1 (Pisces, Literature study)



# RAPTOR 1K TRUCK BED COATING BLACK AEROSOL

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

<b>methyl acetate (79-20-9)</b>	
Partition coefficient n-octanol/water (Log Pow)	0.18 (Experimental value, 20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)

<b>reaction mass of <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-hydroxypoly(oxyethylene) and <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)</b>	
LC50 - Fish [1]	2.8 mg/l (96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	4 mg/l (48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
ErC50 algae	> 100 mg/l (72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
BCF - Fish [1]	2658 – 3430 (502 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	4.6 (Experimental value, Equivalent or similar to OECD 117, 25 °C)

<b>Xylene (1330-20-7)</b>	
LC50 - Fish [1]	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
ErC50 algae	4.36 mg/l (OECD 201: Alga, Growth Inhibition Test, 73 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
EC50 72h - Algae [1]	2.2 mg/l
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
BCF - Fish [1]	7.2 – 25.9 (56 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Read-across)
Partition coefficient n-octanol/water (Log Pow)	3.2 (Read-across, 20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.73 (log Koc, Equivalent or similar to OECD 121, Read-across)

<b>ethylbenzene (100-41-4)</b>	
LC50 - Fish [1]	5.1 mg/l Test organisms (species): Menidia menidia
EC50 - Crustacea [1]	1.8 – 2.4 mg/l (US EPA, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)
EC50 72h - Algae [1]	4.9 mg/l Test organisms (species): Skeletonema costatum
EC50 72h - Algae [2]	5.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	7.7 mg/l Test organisms (species): Skeletonema costatum
EC50 96h - Algae [2]	3.6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
BCF - Fish [1]	1 (6 week(s), Oncorhynchus kisutch, Flow-through system, Salt water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	3.6 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.71 (log Koc, PCKOCWIN v1.66, QSAR)
LOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'

### 12.2. Persistence and degradability

<b>n-butyl acetate (123-86-4)</b>	
Persistence and degradability	Readily biodegradable in water.
ThOD	2.21 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.46

<b>acetone (67-64-1)</b>	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.43 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.92 g O <sub>2</sub> /g substance
ThOD	2.2 g O <sub>2</sub> /g substance

<b>carbon black (1333-86-4)</b>	
Persistence and degradability	Biodegradability in soil: not applicable. Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)

# RAPTOR 1K TRUCK BED COATING BLACK AEROSOL

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

<b>carbon black (1333-86-4)</b>	
ThOD	Not applicable (inorganic)
<b>methyl acetate (79-20-9)</b>	
Persistence and degradability	Readily biodegradable in water.
<b>Xylene (1330-20-7)</b>	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
<b>ethylbenzene (100-41-4)</b>	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.44 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.1 g O <sub>2</sub> /g substance
ThOD	3.17 g O <sub>2</sub> /g substance

### 12.3. Bioaccumulative potential

<b>n-butyl acetate (123-86-4)</b>	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Partition coefficient n-octanol/water (Log Pow)	2.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.268 – 1.844 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

<b>acetone (67-64-1)</b>	
Bioaccumulative potential	Not bioaccumulative.
Partition coefficient n-octanol/water (Log Pow)	-0.23 (Test data)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

<b>carbon black (1333-86-4)</b>	
Bioaccumulative potential	Not bioaccumulative.

<b>methyl acetate (79-20-9)</b>	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
BCF - Fish [1]	< 1 (Pisces, Literature study)
Partition coefficient n-octanol/water (Log Pow)	0.18 (Experimental value, 20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)

<b>reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)</b>	
BCF - Fish [1]	2658 – 3430 (502 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	4.6 (Experimental value, Equivalent or similar to OECD 117, 25 °C)

<b>Xylene (1330-20-7)</b>	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
BCF - Fish [1]	7.2 – 25.9 (56 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Read-across)
Partition coefficient n-octanol/water (Log Pow)	3.2 (Read-across, 20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.73 (log Koc, Equivalent or similar to OECD 121, Read-across)

<b>ethylbenzene (100-41-4)</b>	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
BCF - Fish [1]	1 (6 week(s), Oncorhynchus kisutch, Flow-through system, Salt water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	3.6 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.71 (log Koc, PCKOCWIN v1.66, QSAR)

### 12.4. Mobility in soil

<b>n-butyl acetate (123-86-4)</b>	
Surface tension	61.3 mN/m (20 °C, 0.1 %, OECD 115: Surface Tension of Aqueous Solutions)
Ecology - soil	Highly mobile in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.268 – 1.844 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

# RAPTOR 1K TRUCK BED COATING BLACK AEROSOL

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

<b>n-butyl acetate (123-86-4)</b>	
Partition coefficient n-octanol/water (Log Pow)	2.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
<b>acetone (67-64-1)</b>	
Surface tension	23.3 N/m (20 °C)
Ecology - soil	Highly mobile in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Partition coefficient n-octanol/water (Log Pow)	-0.23 (Test data)
<b>carbon black (1333-86-4)</b>	
Surface tension	Not applicable (solid)
Ecology - soil	No (test)data on mobility of the substance available. Not toxic to plants. Not toxic to animals.
<b>methyl acetate (79-20-9)</b>	
Surface tension	24 mN/m (20 °C)
Ecology - soil	Highly mobile in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
Partition coefficient n-octanol/water (Log Pow)	0.18 (Experimental value, 20 °C)
<b>reaction mass of <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-hydroxypoly(oxyethylene) and <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)</b>	
Partition coefficient n-octanol/water (Log Pow)	4.6 (Experimental value, Equivalent or similar to OECD 117, 25 °C)
<b>Xylene (1330-20-7)</b>	
Surface tension	28.01 – 29.76 mN/m (25 °C)
Ecology - soil	Low potential for adsorption in soil. May be harmful to plant growth, blooming and fruit formation.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.73 (log Koc, Equivalent or similar to OECD 121, Read-across)
Partition coefficient n-octanol/water (Log Pow)	3.2 (Read-across, 20 °C)
<b>ethylbenzene (100-41-4)</b>	
Surface tension	71.2 mN/m (23 °C, 0.058 g/l, EU Method A.5: Surface tension)
Ecology - soil	Low potential for adsorption in soil. Toxic to soil organisms.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.71 (log Koc, PCKOCWIN v1.66, QSAR)
Partition coefficient n-octanol/water (Log Pow)	3.6 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)

### 12.5. Other adverse effects

Ozone : Not classified

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

### 14.1. Basic shipping description

In accordance with TDG

#### Transportation of Dangerous Goods

UN-No. (TDG) : UN1950  
TDG Primary Hazard Classes : 2.1 - Class 2.1 - Flammable Gas  
Transport document description (TDG) : UN1950 AEROSOLS, 2.1  
Proper Shipping Name (TDG) : AEROSOLS

# RAPTOR 1K TRUCK BED COATING BLACK AEROSOL

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Hazard labels (TDG) : 2.1 - Flammable gases



TDG Special Provisions : 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment).  
107 - (1) These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL.  
(2) Subsection (1) does not apply to self-defence spray.

Explosive Limit and Limited Quantity Index : 1 L

Excepted quantities (TDG) : E0

Passenger Carrying Road Vehicle or Passenger : 75 L

Carrying Railway Vehicle Index

### 14.2. Transport information/DOT

#### Department of Transport

DOT NA No : UN1950  
UN-No.(DOT) : 1950  
Transport document description (DOT) : UN1950 Aerosols, 2.1  
Proper Shipping Name (DOT) : Aerosols  
Contains Statement Field Selection (DOT) :  
Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115  
Division (DOT) : 2.1  
Hazard labels (DOT) : 2.1 - Flammable gas



Marine pollutant : NO

Dangerous for the environment : No

DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Packaging Non Bulk (49 CFR 173.xxx) : None

DOT Packaging Bulk (49 CFR 173.xxx) : None

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 25 - Protected from sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

Emergency Response Guide (ERG) Number : 126

Other information : No supplementary information available.

### 14.3. Air and sea transport

#### IMDG

UN-No. (IMDG) : 1950

Proper Shipping Name (IMDG) : AEROSOLS

Transport document description (IMDG) : UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS

Class (IMDG) : 2 - Gases

# RAPTOR 1K TRUCK BED COATING BLACK AEROSOL

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### IATA

UN-No. (IATA)	: 1950
Proper Shipping Name (IATA)	: Aerosols, flammable
Transport document description (IATA)	: UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS
Class (IATA)	: 2 - Gases

## SECTION 15: Regulatory information

### 15.1. National regulations

<b>n-butyl acetate (123-86-4)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>acetone (67-64-1)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>carbon black (1333-86-4)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>methyl acetate (79-20-9)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>reaction mass of <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-hydroxypoly(oxyethylene) and <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>Xylene (1330-20-7)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>ethylbenzene (100-41-4)</b>
Listed on the Canadian DSL (Domestic Substances List)

### 15.2. International regulations

<b>n-butyl acetate (123-86-4)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>acetone (67-64-1)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>carbon black (1333-86-4)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>methyl acetate (79-20-9)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>reaction mass of <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-hydroxypoly(oxyethylene) and <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>Xylene (1330-20-7)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>ethylbenzene (100-41-4)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory

## SECTION 16: Other information

SDS Major/Minor	: None
Issue date	: 09-02-2020

Full text of H-phrases:

H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways

# RAPTOR 1K TRUCK BED COATING BLACK AEROSOL

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

SDS Canada U-POL

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*