

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Product Reference code:according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SDS Ref. (EU): RMUBAL-R-SDS Issue date: 02/09/2020 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : RAPTOR 1K MULTI USE PROTECTIVE COATING AEROSOL

UFI : \$591-60Q9-600F-NKYW

Product code : RMUB/AL
Vaporizer : Aerosol
Product group : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public

Main use category : Industrial use, Professional use

Use of the substance/mixture : Coatings and paints, thinners, paint removers

Function or use category : Topcoat

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer Importer

U-POL Limited U-POL Netherlands B.V. Denington Road U-pol Netherlands B.V.

NN8 2QH Wellingborough - United Kingdom 1101BA Amsterdam - Netherlands

T +44 (0) 1933 230310 T +31 20 240 2216

<u>technicalsupport@u-pol.com</u> - <u>www.u-pol.com</u> - <u>www.u-pol.com</u> - <u>www.u-pol.com</u> - <u>www.u-pol.com</u>

1.4. Emergency telephone number

Emergency number : CHEMTREC: +44 (0) 870 8200418 (24 hrs)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	NHS England, Scotland & Wales	-	Call 111 or a Doctor	In Northern Ireland, contact your local GP or pharmacist during normal hours (www.gpoutofhours.h scni.net)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Serious eye damage/eye irritation, Category 2 H319

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Skin sensitisation, Category 1 H317
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)







GHS02

GHS07

GHS09

Signal word (CLP) : Danger

Contains : reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-

hydroxypoly(oxyethylene) and $\alpha\text{-}3\text{-}(3\text{-}(2H\text{-}benzotriazol\text{-}2\text{-}yl)\text{-}5\text{-}tert\text{-}butyl\text{-}4\text{-}hydroxyphenyl)propionyl-}\omega\text{-}3\text{-}(3\text{-}(2H\text{-}benzotriazol\text{-}2\text{-}yl)\text{-}5\text{-}tert\text{-}butyl\text{-}4\text{-}}$

hydroxyphenyl)propionyloxypoly(oxyethylene); reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate; methyl acetate

Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.

H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.
P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear eye protection, protective clothing, protective gloves.

P391 - Collect spillage. P405 - Store locked up.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122

°F.

P501 - Dispose of contents and container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

EUH-statements : EUH066 - Repeated exposure may cause skin dryness or cracking.

Unknown acute toxicity (CLP) - SDS : 1.86% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation

(Vapours))

2.3. Other hazards

Component	
methyl acetate (79-20-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
n-butyl acetate (123-86-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

acetone (67-64-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
trizinc bis(orthophosphate) (7779-90-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Xylene (1330-20-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Ethylbenzene (100-41-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
methyl acetate	(CAS-No.) 79-20-9 (EC-No.) 201-185-2 (EC Index-No.) 607-021-00-X (REACH-no) 01-2119459211-47	10 – 20	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
n-butyl acetate substance with a Community workplace exposure limit	(CAS-No.) 123-86-4 (EC-No.) 204-658-1 (EC Index-No.) 607-025-00-1 (REACH-no) 01-2119485493-29	10 – 20	Flam. Liq. 3, H226 STOT SE 3, H336
acetone substance with a Community workplace exposure limit	(CAS-No.) 67-64-1 (EC-No.) 200-662-2 (EC Index-No.) 606-001-00-8 (REACH-no) 01-2119471330-49	10 – 20	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
trizinc bis(orthophosphate)	(CAS-No.) 7779-90-0 (EC-No.) 231-944-3 (EC Index-No.) 030-011-00-6 (REACH-no) 01-2119485044-40	3 – 5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Xylene substance with a Community workplace exposure limit (Note C)	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index-No.) 601-022-00-9 (REACH-no) 01-2119488216-32	3 – 5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
heptan-2-one substance with a Community workplace exposure limit	(CAS-No.) 110-43-0 (EC-No.) 203-767-1 (EC Index-No.) 606-024-00-3 (REACH-no) 01-2119902391-49	1 – 2.5	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 STOT SE 3, H336

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ethylbenzene substance with a Community workplace exposure limit	(CAS-No.) 100-41-4 (EC-No.) 202-849-4 (EC Index-No.) 601-023-00-4 (REACH-no) 01-2119489370-35	1 – 2.5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	(EC-No.) 400-830-7 (EC Index-No.) 607-176-00-3 (REACH-no) 01-0000015075-76	0.3 – 1	Skin Sens. 1A, H317 Aquatic Chronic 2, H411
reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	(CAS-No.) 1065336-91-5 (EC-No.) 915-687-0 (REACH-no) 01-2119491304-40	0.1 – 0.3	Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash

occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : May cause an allergic skin reaction. Repeated exposure may cause skin dryness or

cracking.

Symptoms/effects after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

02/09/2020 (Issue date) EN (English) 4/29

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing

vapours, spray, fume. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Mechanically recover the product.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn,

even after use. Use only outdoors or in a well-ventilated area. Avoid breathing vapours, spray, fume. Avoid contact with skin and eyes. Wear personal protective equipment.

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash

contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

up. Glore in a won vortained place. Neep container lightly discoul. Neep

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

n-butyl acetate (123-86-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	n-Butyl acetate
IOEL TWA	241 mg/m³
IOEL TWA [ppm]	50 ppm
IOEL STEL	723 mg/m³
IOEL STEL [ppm]	150 ppm

02/09/2020 (Issue date) EN (English) 5/29

Safety Data Sheet

n-butyl acetate (123-86-4)	
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831
Ireland - Occupational Exposure Limits	
Local name	Butyl acetate
OEL TWA [1]	710 mg/m³
OEL TWA [2]	150 ppm
OEL STEL	950 mg/m³
OEL STEL [ppm]	200 ppm
Regulatory reference	Chemical Agents Code of Practice 2020
United Kingdom - Occupational Exposure Limits	
Local name	Butyl acetate
WEL TWA (OEL TWA) [1]	724 mg/m³
WEL TWA (OEL TWA) [2]	150 ppm
WEL STEL (OEL STEL)	966 mg/m³
WEL STEL (OEL STEL) [ppm]	200 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

EU - Indicative Occupational Exposure Limit (IOEL) Local name			
Local name Acetone	acetone (67-64-1)		
IOEL TWA 1210 mg/m³ IOEL TWA [ppm] 500 ppm Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Ireland - Occupational Exposure Limits Local name Acetone OEL TWA [1] 1210 mg/m³ OEL TWA [2] 500 ppm Notes (IE) IOELV (Indicative Occupational Exposure Limit Values) Regulatory reference Chemical Agents Code of Practice 2020 Ireland - Biological limit values Local name Acetone BLV 50 mg/l Parameter: acetone - Medium: urine - Sampling time: End of shift - Notations: Ns (Non-specific) Regulatory reference Biological Monitoring Guidelines (HSA, 2011) United Kingdom - Occupational Exposure Limits Local name Acetone WEL TWA (OEL TWA) [1] 1210 mg/m³ WEL TWA (OEL TWA) [2] 500 ppm	EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA [ppm] 500 ppm Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Ireland - Occupational Exposure Limits Local name Acetone OEL TWA [1] 1210 mg/m³ OEL TWA [2] 500 ppm Notes (IE) IOELV (Indicative Occupational Exposure Limit Values) Regulatory reference Chemical Agents Code of Practice 2020 Ireland - Biological limit values Local name Acetone BLV 50 mg/l Parameter: acetone - Medium: urine - Sampling time: End of shift - Notations: Ns (Non-specific) Regulatory reference Biological Monitoring Guidelines (HSA, 2011) United Kingdom - Occupational Exposure Limits Local name Acetone WEL TWA (OEL TWA) [1] 1210 mg/m³ WEL TWA (OEL TWA) [2] 500 ppm	Local name	Acetone	
Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Ireland - Occupational Exposure Limits Local name Acetone OEL TWA [1] 1210 mg/m³ OEL TWA [2] 500 ppm Notes (IE) IOELV (Indicative Occupational Exposure Limit Values) Regulatory reference Chemical Agents Code of Practice 2020 Ireland - Biological limit values Local name Acetone BLV 50 mg/l Parameter: acetone - Medium: urine - Sampling time: End of shift - Notations: Ns (Non-specific) Regulatory reference Biological Monitoring Guidelines (HSA, 2011) United Kingdom - Occupational Exposure Limits Local name Acetone WEL TWA (OEL TWA) [1] 1210 mg/m³ WEL TWA (OEL TWA) [2] 500 ppm	IOEL TWA	1210 mg/m³	
Ireland - Occupational Exposure Limits Local name Acetone OEL TWA [1] 1210 mg/m³ OEL TWA [2] 500 ppm Notes (IE) IOELV (Indicative Occupational Exposure Limit Values) Regulatory reference Chemical Agents Code of Practice 2020 Ireland - Biological limit values Local name Acetone BLV 50 mg/l Parameter: acetone - Medium: urine - Sampling time: End of shift - Notations: Ns (Non-specific) Regulatory reference Biological Monitoring Guidelines (HSA, 2011) United Kingdom - Occupational Exposure Limits Local name Acetone WEL TWA (OEL TWA) [1] 1210 mg/m³ WEL TWA (OEL TWA) [2] 500 ppm	IOEL TWA [ppm]	500 ppm	
Local name Acetone OEL TWA [1] 1210 mg/m³ OEL TWA [2] 500 ppm Notes (IE) Regulatory reference Chemical Agents Code of Practice 2020 Ireland - Biological limit values Local name Acetone BLV 50 mg/l Parameter: acetone - Medium: urine - Sampling time: End of shift - Notations: Ns (Non-specific) Regulatory reference Biological Monitoring Guidelines (HSA, 2011) United Kingdom - Occupational Exposure Limits Local name Acetone WEL TWA (OEL TWA) [1] 1210 mg/m³ WEL TWA (OEL TWA) [2] 500 ppm	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
OEL TWA [1] 1210 mg/m³ OEL TWA [2] 500 ppm Notes (IE) IOELV (Indicative Occupational Exposure Limit Values) Regulatory reference Chemical Agents Code of Practice 2020 Ireland - Biological limit values Local name Acetone BLV 50 mg/l Parameter: acetone - Medium: urine - Sampling time: End of shift - Notations: Ns (Non-specific) Regulatory reference Biological Monitoring Guidelines (HSA, 2011) United Kingdom - Occupational Exposure Limits Local name Acetone WEL TWA (OEL TWA) [1] 1210 mg/m³ WEL TWA (OEL TWA) [2] 500 ppm	Ireland - Occupational Exposure Limits		
OEL TWA [2] Notes (IE) IOELV (Indicative Occupational Exposure Limit Values) Regulatory reference Chemical Agents Code of Practice 2020 Ireland - Biological limit values Local name Acetone BLV 50 mg/l Parameter: acetone - Medium: urine - Sampling time: End of shift - Notations: Ns (Non-specific) Regulatory reference Biological Monitoring Guidelines (HSA, 2011) United Kingdom - Occupational Exposure Limits Local name Acetone WEL TWA (OEL TWA) [1] 1210 mg/m³ WEL TWA (OEL TWA) [2] 500 ppm	Local name	Acetone	
Notes (IE) Regulatory reference Chemical Agents Code of Practice 2020 Ireland - Biological limit values Local name Acetone BLV 50 mg/l Parameter: acetone - Medium: urine - Sampling time: End of shift - Notations: Ns (Non-specific) Regulatory reference Biological Monitoring Guidelines (HSA, 2011) United Kingdom - Occupational Exposure Limits Local name Acetone WEL TWA (OEL TWA) [1] 1210 mg/m³ WEL TWA (OEL TWA) [2] 500 ppm	OEL TWA [1]	1210 mg/m³	
Regulatory reference Chemical Agents Code of Practice 2020 Ireland - Biological limit values Local name Acetone BLV 50 mg/l Parameter: acetone - Medium: urine - Sampling time: End of shift - Notations: Ns (Non-specific) Regulatory reference Biological Monitoring Guidelines (HSA, 2011) United Kingdom - Occupational Exposure Limits Local name Acetone WEL TWA (OEL TWA) [1] 1210 mg/m³ WEL TWA (OEL TWA) [2] 500 ppm	OEL TWA [2]	500 ppm	
Ireland - Biological limit values Acetone	Notes (IE)	IOELV (Indicative Occupational Exposure Limit Values)	
Local name Acetone BLV 50 mg/l Parameter: acetone - Medium: urine - Sampling time: End of shift - Notations: Ns (Non-specific) Regulatory reference Biological Monitoring Guidelines (HSA, 2011) United Kingdom - Occupational Exposure Limits Local name Acetone WEL TWA (OEL TWA) [1] 1210 mg/m³ WEL TWA (OEL TWA) [2] 500 ppm	Regulatory reference	Chemical Agents Code of Practice 2020	
BLV 50 mg/l Parameter: acetone - Medium: urine - Sampling time: End of shift - Notations: Ns (Non-specific) Regulatory reference Biological Monitoring Guidelines (HSA, 2011) United Kingdom - Occupational Exposure Limits Local name Acetone WEL TWA (OEL TWA) [1] 1210 mg/m³ WEL TWA (OEL TWA) [2] 500 ppm	Ireland - Biological limit values		
Regulatory reference Biological Monitoring Guidelines (HSA, 2011) United Kingdom - Occupational Exposure Limits Local name Acetone WEL TWA (OEL TWA) [1] 1210 mg/m³ WEL TWA (OEL TWA) [2] 500 ppm	Local name	Acetone	
United Kingdom - Occupational Exposure Limits Local name Acetone WEL TWA (OEL TWA) [1] 1210 mg/m³ WEL TWA (OEL TWA) [2] 500 ppm	BLV		
Local name Acetone WEL TWA (OEL TWA) [1] 1210 mg/m³ WEL TWA (OEL TWA) [2] 500 ppm	Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)	
WEL TWA (OEL TWA) [1] 1210 mg/m³ WEL TWA (OEL TWA) [2] 500 ppm	United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [2] 500 ppm	Local name	Acetone	
1 11	WEL TWA (OEL TWA) [1]	1210 mg/m³	
WEL STEL (OEL STEL) 3620 mg/m³	WEL TWA (OEL TWA) [2]	500 ppm	
	WEL STEL (OEL STEL)	3620 mg/m³	
WEL STEL (OEL STEL) [ppm] 1500 ppm	WEL STEL (OEL STEL) [ppm]	1500 ppm	
Regulatory reference EH40/2005 (Fourth edition, 2020). HSE	Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

Safety Data Sheet

methyl acetate (79-20-9)	
Ireland - Occupational Exposure Limits	
Local name	Methyl acetate
OEL TWA [1]	610 mg/m³
OEL TWA [2]	200 ppm
OEL STEL	760 mg/m³
OEL STEL [ppm]	250 ppm
Regulatory reference Chemical Agents Code of Practice 2020	
United Kingdom - Occupational Exposure Limits	
Local name	Methyl acetate
WEL TWA (OEL TWA) [1]	616 mg/m ³
WEL TWA (OEL TWA) [2]	200 ppm
WEL STEL (OEL STEL)	770 mg/m³
WEL STEL (OEL STEL) [ppm]	250 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

heptan-2-one (110-43-0)			
EU - Indicative Occupational Exposure Limit (IOEL)	EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Heptan-2-one		
IOEL TWA	238 mg/m³		
IOEL TWA [ppm]	50 ppm		
IOEL STEL	475 mg/m³		
IOEL STEL [ppm]	100 ppm		
Notes	Skin		
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC		
Ireland - Occupational Exposure Limits			
Local name	Heptan-2-one [Methyl-n-amyl-ketone]		
OEL TWA [1]	238 mg/m³		
OEL TWA [2]	50 ppm		
OEL STEL	475 mg/m³		
OEL STEL [ppm]	100 ppm		
Notes (IE)	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)		
Regulatory reference	Chemical Agents Code of Practice 2020		
United Kingdom - Occupational Exposure Limits			
Local name	Heptan-2-one		
WEL TWA (OEL TWA) [1]	237 mg/m³		
WEL TWA (OEL TWA) [2]	50 ppm		
WEL STEL (OEL STEL)	475 mg/m³		
WEL STEL (OEL STEL) [ppm]	100 ppm		

Safety Data Sheet

heptan-2-one (110-43-0)	
Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Xylene (1330-20-7)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Xylene, mixed isomers, pure	
IOEL TWA	221 mg/m³	
IOEL TWA [ppm]	50 ppm	
IOEL STEL	442 mg/m³	
IOEL STEL [ppm]	100 ppm	
Notes	Skin	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
Ireland - Occupational Exposure Limits		
Local name	Xylene, mixed isomers	
OEL TWA [1]	221 mg/m³	
OEL TWA [2]	50 ppm	
OEL STEL	442 mg/m³	
OEL STEL [ppm]	100 ppm	
Notes (IE)	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)	
Regulatory reference	Chemical Agents Code of Practice 2020	
Ireland - Biological limit values		
Local name	Xylene	
BLV	1.5 g/g creatinine Parameter: methylhippuric acids - Medium: urine - Sampling time: End of Shift	
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)	
United Kingdom - Occupational Exposure Limits		
Local name	Xylene	
WEL TWA (OEL TWA) [1]	220 mg/m³	
WEL TWA (OEL TWA) [2]	50 ppm	
WEL STEL (OEL STEL)	441 mg/m³	
WEL STEL (OEL STEL) [ppm]	100 ppm	
Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
United Kingdom - Biological limit values		
Local name	Xylene, o-, m-, p- or mixed isomers	
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ethylbenzene (100-41-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Ethylbenzene
IOEL TWA	442 mg/m³
IOEL TWA [ppm]	100 ppm
IOEL STEL	884 mg/m³
IOEL STEL [ppm]	200 ppm
Notes	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Ireland - Occupational Exposure Limits	
Local name	Ethylbenzene
OEL TWA [1]	442 mg/m³
OEL TWA [2]	100 ppm
OEL STEL	884 mg/m³
OEL STEL [ppm]	200 ppm
Notes (IE)	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2020
Ireland - Biological limit values	
Local name	Ethyl benzene
BLV	0.7 g/g creatinine Parameter: mandelic acid and phenylglyoxylic acid - Medium: urine - Sampling time: End of shift at end of workweek - Notations: Ns (Non-specific), Sq (Semi-quantitative) Parameter: ethylbenzene - Medium: end-exhaled air - Sampling time: Not critical - Notations: Sq (Semi-quantitative)
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)
United Kingdom - Occupational Exposure Limits	
Local name	Ethylbenzene
WEL TWA (OEL TWA) [1]	441 mg/m³
WEL TWA (OEL TWA) [2]	100 ppm
WELCTEL (OFLICTEL)	552 mg/m³
WEL STEL (OEL STEL)	
WEL STEL (OEL STEL) [ppm]	125 ppm
<u> </u>	125 ppm Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

8.1.4. DNEL and PNEC

n-butyl acetate (123-86-4)	
DNEL/DMEL (Workers)	
Acute - systemic effects, dermal	11 mg/kg bw/day
Acute - systemic effects, inhalation	600 mg/m³
Acute - local effects, inhalation	600 mg/m³
Long-term - systemic effects, dermal	11 mg/kg bw/day
Long-term - systemic effects, inhalation	300 mg/m³
Long-term - local effects, inhalation	300 mg/m³
DNEL/DMEL (General population)	
Acute - systemic effects, dermal	6 mg/kg bw/day
Acute - systemic effects, inhalation	300 mg/m³
Acute - systemic effects, oral	2 mg/kg bw/day
Acute - local effects, inhalation	300 mg/m³
Long-term - systemic effects,oral	2 mg/kg bw/day
Long-term - systemic effects, inhalation	35.7 mg/m³
Long-term - systemic effects, dermal	6 mg/kg bw/day
Long-term - local effects, inhalation	35.7 mg/m³
PNEC (Water)	
PNEC aqua (freshwater)	0.18 mg/l
PNEC aqua (marine water)	0.018 mg/l
PNEC aqua (intermittent, freshwater)	0.36 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0.981 mg/kg dwt
PNEC sediment (marine water)	0.0981 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.0903 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	35.6 mg/l

acetone (67-64-1)		
DNEL/DMEL (Workers)		
Acute - local effects, inhalation	2420 mg/m³	
Long-term - systemic effects, dermal	186 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	1210 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	62 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	200 mg/m³	
Long-term - systemic effects, dermal	62 mg/kg bodyweight/day	
PNEC (Water)		
PNEC aqua (freshwater)	10.6 mg/l	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

PNEC aqua (marine water)	1.06 mg/l
PNEC aqua (intermittent, freshwater)	21 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	30.4 mg/kg dwt
PNEC sediment (marine water)	3.04 mg/kg dwt
PNEC (Soil)	
PNEC soil	29.5 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	100 mg/l

methyl acetate (79-20-9)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	88 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	610 mg/m³	
Long-term - local effects, inhalation	305 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	44 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	131 mg/m³	
Long-term - systemic effects, dermal	44 mg/kg bodyweight/day	
Long-term - local effects, inhalation	152 mg/m³	
PNEC (Water)		
PNEC aqua (freshwater)	0.12 mg/l	
PNEC aqua (marine water)	0.012 mg/l	
PNEC aqua (intermittent, freshwater)	1.2 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	0.128 mg/kg dwt	
PNEC sediment (marine water)	0.0128 mg/kg dwt	
PNEC (Soil)		
PNEC soil	0.0416 mg/kg dwt	
PNEC (Oral)		
PNEC oral (secondary poisoning)	20.4 mg/kg food	
PNEC (STP)		
PNEC sewage treatment plant	600 mg/l	

reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

DNEL/DMEL (Workers)

DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	0.05 mg/kg bw/day	
Long-term - systemic effects, inhalation	0.35 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	0.025 mg/kg bw/day	
Long-term - systemic effects, inhalation	0.085 mg/m³	

Safety Data Sheet

Long-term - systemic effects, dermal	0.25 mg/kg bw/day	
PNEC (Water)		
PNEC aqua (freshwater)	0.0023 mg/l	
PNEC aqua (marine water)	0.00023 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	3.37 mg/kg dwt	
PNEC sediment (marine water)	0.337 mg/kg dwt	
PNEC (Soil)		
PNEC soil	2 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	10 mg/l	

reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, inhalation	0.68 mg/m³ (DGUV DNEL List 2019)

heptan-2-one (110-43-0)		
DNEL/DMEL (Workers)		
Acute - systemic effects, inhalation	1516 mg/m³	
Long-term - systemic effects, dermal	54.27 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	394.25 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	23.32 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	84.31 mg/m³	
Long-term - systemic effects, dermal	23.32 mg/kg bodyweight/day	
PNEC (Water)		
PNEC aqua (freshwater)	0.0982 mg/l	
PNEC aqua (marine water)	0.00982 mg/l	
PNEC aqua (intermittent, freshwater)	0.982 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	1.89 mg/kg dwt	
PNEC sediment (marine water)	0.189 mg/kg dwt	
PNEC (Soil)		
PNEC soil	0.321 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	12.5 mg/l	

Xylene (1330-20-7)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	289 mg/m³
Acute - local effects, inhalation	289 mg/m³
Long-term - systemic effects, dermal	180 mg/kg bodyweight/day

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Long-term - systemic effects, inhalation	77 mg/m³	
Long-term - local effects, inhalation	77 mg/m³	
DNEL/DMEL (General population)		
Acute - systemic effects, inhalation	174 mg/m³	
Acute - local effects, inhalation	174 mg/m³	
Long-term - systemic effects,oral	1.6 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	14.8 mg/m³	
Long-term - systemic effects, dermal	108 mg/kg bodyweight/day	
Long-term - local effects, inhalation	65.3 mg/m³	
PNEC (Water)		
PNEC aqua (freshwater)	0.327 mg/l	
PNEC aqua (marine water)	0.327 mg/l	
PNEC aqua (intermittent, freshwater)	0.327 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	12.46 mg/kg dwt	
PNEC sediment (marine water)	12.46 mg/kg dwt	
PNEC (Soil)		
PNEC soil	2.31 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	6.58 mg/l	

Ethylbenzene (100-41-4)		
DNEL/DMEL (Workers)		
Acute - local effects, inhalation	293 mg/m³	
Long-term - systemic effects, dermal	180 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	77 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	1.6 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	15 mg/m³	
PNEC (Water)		
PNEC aqua (freshwater)	0.1 mg/l	
PNEC aqua (marine water)	0.01 mg/l	
PNEC aqua (intermittent, freshwater)	0.1 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	13.7 mg/kg dwt	
PNEC sediment (marine water)	1.37 mg/kg dwt	
PNEC (Soil)		
PNEC soil	2.68 mg/kg dwt	
PNEC (Oral)		
PNEC oral (secondary poisoning)	0.02 g/kg food	
PNEC (STP)		
PNEC sewage treatment plant	9.6 mg/l	

02/09/2020 (Issue date) EN (English) 13/29

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

: Liquid Physical state Colour : Black. Appearance : Aerosol. Odour : aromatic. Odour threshold : Not available : Not available Melting point Freezing point : Not available Boiling point : Not available

Flammability : Extremely flammable aerosol.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

: Not available Auto-ignition temperature Decomposition temperature : Not available рΗ Not available Not available Viscosity, kinematic Solubility Not available Partition coefficient n-octanol/water (Log Kow) Not available Vapour pressure Not available Vapour pressure at 50 °C Not available Density : 0.96 g/cm³ Relative density : Not available Relative vapour density at 20 °C : Not available : Not applicable Particle size Particle size distribution : Not applicable : Not applicable Particle shape : Not applicable Particle aspect ratio Particle aggregation state : Not applicable Particle agglomeration state : Not applicable Particle specific surface area : Not applicable Particle dustiness : Not applicable

9.2. Other information

VOC content : 598 g/l

Gas group : Press. Gas (Liq.)

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 69.45419100000002

9.2.2. Other safety characteristics

Gas group : Press. Gas (Liq.)

VOC content : 598 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified

Safety Data Sheet

n-butyl acetate (123-86-4)	
LD50 oral rat	10760 – 12789 mg/kg bodyweight (Equivalent or similar to OECD 423, Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	14112 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat [ppm]	390 ppm/4h
LC50 Inhalation - Rat (Vapours)	> 21 mg/l/4h (4 h, OECD Test Guideline 403, rat, vapours)

acetone (67-64-1)	
LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female
LD50 dermal rabbit	20000 mg/kg (Equivalent or similar to OECD 402, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4

quartz (14808-60-7)	
LD50 oral rat	> 500 mg/kg

carbon black (1333-86-4)	
LD50 oral rat	> 8000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LC50 Inhalation - Rat	> 4.6 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Experimental value, Inhalation (dust))

methyl acetate (79-20-9)	
LD50 oral rat	6482 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	49 mg/l

trizinc bis(orthophosphate) (7779-90-0)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LC50 Inhalation - Rat	> 5.41 mg/l/4h (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male/female, Read-across, Inhalation (dust))

lithium chloride (7447-41-8)	
LD50 oral rat	526 mg/kg bodyweight Animal: rat, Animal sex: male
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: EPA OPP 81-2 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 5.57 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)

Safety Data Sheet

reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	
LD50 oral rat	> 5000 mg/kg (OECD Guideline No. 401 (equivalent to Annex V), limit test, rat, male/female)
LD50 dermal rat	> 2000 mg/kg (OECD Guideline No. 402 (equivalent to Annex V), limit test, rat, male/female)
LC50 Inhalation - Rat	5800 mg/l (OECD Guideline 403, 14d, rat)

reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)	
LD50 oral rat	3230 mg/kg (OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), rat, male/female)
LD50 dermal rat	> 3170 mg/kg (OECD Guideline 402 (Acute Dermal Toxicity), read-across,

heptan-2-one (110-43-0)	
LD50 oral rat	≈ 1600 mg/kg bodyweight Animal: rat
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
LC50 Inhalation - Rat	> 16.7 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation))

C22-30 chlorinated parrafin (chlorination: 42-48%) (63449-39-8)	
LD50 oral rat	> 11700 mg/kg bodyweight Animal: rat, Guideline: EPA OPP 81-1 (Acute Oral Toxicity)
LD50 oral	> 23400 mg/kg bodyweight Animal: mouse, Guideline: EPA OPP 81-1 (Acute Oral Toxicity)
LD50 dermal rabbit	> 13900 mg/kg

LPG, liquefied, under pressure (68476-85-7)	
LC50 Inhalation - Rat	658 mg/l (4 h, Rat, Inhalation)

Xylene (1330-20-7)	
LD50 oral rat	3523 mg/kg bodyweight (Equivalent or similar to EU Method B.1: Acute Toxicity (Oral), Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	12126 mg/kg (Non-GLP, read-across from supporting substance, single dermal dose under occlusion followed by observation for 14 days)
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male
LC50 Inhalation - Rat [ppm]	6700 ppm/4h (EU Method B.2 (Acute Toxicity (Inhalation)), 4h, rat, male)

Ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg (Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	15432 mg/kg bodyweight (24 h, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat	17.8 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours))

Methyl methacrylate (80-62-6)	
LD50 oral rat	7900 mg/kg

Safety Data Sheet

> 5000 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
4632 ppm/4h
1.86% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))
Not classified
Causes serious eye irritation.
May cause an allergic skin reaction.
Not classified
Not classified
3 - Not classifiable
2B - Possibly carcinogenic to humans
48%) (63449-39-8)
> 3750 mg/kg bodyweight Animal: rat, Animal sex: male
100 mg/kg bodyweight Animal: rat, Animal sex: female
Not classified
11298 mg/kg bodyweight Animal: mouse, Animal sex: female
900 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)
May cause drowsiness or dizziness.
May cause drowsiness or dizziness.
May cause drowsiness or dizziness.
May cause drowsiness or dizziness.
May cause drowsiness or dizziness.
<u>'</u>
May cause respiratory irritation.

02/09/2020 (Issue date) EN (English) 18/29

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Methyl methacrylate (80-62-6)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : Not classified

methyl acetate (79-20-9)	
LOAEC (inhalation, rat, vapour, 90 days)	2000 mg/l
NOAEC (inhalation, rat, vapour, 90 days)	1057 mg/m³

Xylene (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Ethylbenzene (100-41-4)	
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity in Rodents)
STOT-repeated exposure	May cause damage to organs (hearing sense) through prolonged or repeated exposure.

n-butyl methacrylate (97-88-1)	
LOAEC (inhalation, rat, gas, 90 days)	952 ppm Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28- Day Study)
NOAEL (oral, rat, 90 days)	120 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Aspiration hazard : Not classified

RAPTOR 1K MULTI USE PROTECTIVE COATING AEROSOL	
Vaporizer	Aerosol

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term : Not classified

(acute)

Hazardous to the aquatic environment, long-term : Toxic to aquatic life with long lasting effects.

(chronic)

n-butyl acetate (123-86-4)	
LC50 - Fish [1]	18 mg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	62 mg/l (Leuciscus idus, static system)
EC50 - Crustacea [1]	44 mg/l Test organisms (species): Daphnia sp.

02/09/2020 (Issue date) EN (English) 19/29

Safety Data Sheet

ErC50 algae

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

EC50 72h - Algae [1]	674.7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC (chronic)	23 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic crustacea	23 mg/l

acetone (67-64-1)	
LC50 - Fish [1]	5540 mg/l (EU Method C.1, 96 h, Salmo gairdneri, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 96h - Algae [1]	> 7000 mg/l (Selenastrum capricornutum, Static system, Fresh water, Experimental value, Nominal concentration)
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

methyl acetate (79-20-9)	
LC50 - Fish [1]	250 – 350 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	1026.7 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 120 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

trizinc bis(orthophosphate) (7779-90-0)	
LC50 - Fish [1]	0.169 mg/l (ASTM E729-88, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Read-across, Nominal concentration)

reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

LC50 - Fish [1]

2.8 mg/l (96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)

EC50 - Crustacea [1]

4 mg/l (48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)

> 100 mg/l (72 h, Pseudokirchneriella subcapitata, Static system, Fresh water,

heptan-2-one (110-43-0)	
LC50 - Fish [1]	131 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	> 90.1 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	98.2 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	75.5 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names:

Experimental value, Nominal concentration)

Raphidocelis subcapitata, Selenastrum capricornutum)

Xylene (1330-20-7)	
LC50 - Fish [1]	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
EC50 72h - Algae [1]	2.2 mg/l

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

	4.36 mg/l (OECD 201: Alga, Growth Inhibition Test, 73 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

Ethylbenzene (100-41-4)	
LC50 - Fish [1]	5.1 mg/l Test organisms (species): Menidia menidia
EC50 - Crustacea [1]	1.8 – 2.4 mg/l (US EPA, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)
EC50 72h - Algae [1]	4.9 mg/l Test organisms (species): Skeletonema costatum
EC50 72h - Algae [2]	5.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	7.7 mg/l Test organisms (species): Skeletonema costatum
EC50 96h - Algae [2]	3.6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'

12.2. Persistence and degradability

n-butyl acetate (123-86-4)	
Persistence and degradability	Readily biodegradable in water.
ThOD	2.21 g O ₂ /g substance
BOD (% of ThOD)	0.46

acetone (67-64-1)	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance
Chemical oxygen demand (COD)	1.92 g O ₂ /g substance
ThOD	2.2 g O₂/g substance
BOD (% of ThOD)	0.872 (20 day(s), Literature study)

methyl acetate (79-20-9)	
Persistence and degradability	Readily biodegradable in water.

trizinc bis(orthophosphate) (7779-90-0)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

heptan-2-one (110-43-0)	
Persistence and degradability	Readily biodegradable in water.
BOD (% of ThOD)	0.44

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830		
Xylene (1330-20-7)		
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.	
Ethylbenzene (100-41-4)	I	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.	
Biochemical oxygen demand (BOD)	1.44 g O₂/g substance	
Chemical oxygen demand (COD)	2.1 g O₂/g substance	
ThOD	3.17 g O₂/g substance	
12.3. Bioaccumulative potential		
n-butyl acetate (123-86-4)		
BCF - Fish [1]	15.3 (Calculated value)	
Partition coefficient n-octanol/water (Log Pow)	2.3 (Test data, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	
acetone (67-64-1)	0.00 (Pinns)	
BCF - Fish [1]	0.69 (Pisces)	
BCF - Other aquatic organisms [1]	3 (BCFWIN, Calculated value)	
Partition coefficient n-octanol/water (Log Pow)	-0.24 (Test data)	
Bioaccumulative potential	Not bioaccumulative.	
methyl acetate (79-20-9)		
BCF - Fish [1]	< 1 (Pisces, Literature study)	
Partition coefficient n-octanol/water (Log Pow)	0.18 (Experimental value, 20 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
trining his/orthornhoomhata) (7770,00,0)		
trizinc bis(orthophosphate) (7779-90-0)	440 00000 (04 1 / /) 0	
BCF - Other aquatic organisms [1]	116 – 60960 (21 day(s), Gammarus sp., Semi-static system, Salt water, Read-across, Fresh weight)	
Bioaccumulative potential	High potential for bioaccumulation (BCF > 5000).	
reaction mass of α-3-(3-(2H-benzotriazol-2-yl) 3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene	-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α- oxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4- e)	
BCF - Fish [1]	2658 – 3430 (502 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value)	
Partition coefficient n-octanol/water (Log Pow)	4.6 (Experimental value, Equivalent or similar to OECD 117, 25 °C)	
henten 2 ene (410 42 0)		
heptan-2-one (110-43-0) Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
Dioaccumulative potential	Low potential for bloaccumulation (Log Now < 4).	
Xylene (1330-20-7)		
BCF - Fish [1]	7.2 – 25.9 (56 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Read-	

02/09/2020 (Issue date)	EN (English)	22/29
-------------------------	--------------	-------

3.2 (Read-across, 20 °C)

across)

Partition coefficient n-octanol/water (Log Pow)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Ethylbenzene (100-41-4)	
BCF - Fish [1]	1 (6 week(s), Oncorhynchus kisutch, Flow-through system, Salt water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	3.6 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)

Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

Bioaccumulative potential

n-butyl acetate (123-86-4)	
Surface tension	0.0163 N/m (20 °C)
Partition coefficient n-octanol/water (Log Koc)	1.268 – 1.844 (log Koc, SRC PCKOCWIN v2.0, QSAR)
Ecology - soil	Low potential for adsorption in soil.

acetone (67-64-1)	
Surface tension	0.0237 N/m
Ecology - soil	No (test)data on mobility of the substance available.

methyl acetate (79-20-9)	
Surface tension	24 mN/m (20 °C)
Partition coefficient n-octanol/water (Log Koc)	0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
Ecology - soil	Highly mobile in soil.

trizinc bis(orthophosphate) (7779-90-0)	
Ecology - soil	Adsorbs into the soil.

heptan-2-one (110-43-0)	
Surface tension	0.0591 N/m (21.6 °C, EU Method A.5: Surface tension)
Partition coefficient n-octanol/water (Log Koc)	1.45 (log Koc, EU Method C.19, Experimental value)
Ecology - soil	Highly mobile in soil.

Xylene (1330-20-7)	
Surface tension	28.01 – 29.76 mN/m (25 °C)
Partition coefficient n-octanol/water (Log Koc)	2.73 (log Koc, Equivalent or similar to OECD 121, Read-across)
Ecology - soil	Low potential for adsorption in soil. May be harmful to plant growth, blooming and fruit formation.

Ethylbenzene (100-41-4)	
Surface tension	71.2 mN/m (23 °C, 0.058 g/l, EU Method A.5: Surface tension)
Partition coefficient n-octanol/water (Log Koc)	2.71 (log Koc, PCKOCWIN v1.66, QSAR)
Ecology - soil	Low potential for adsorption in soil. Toxic to soil organisms.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.5. Results of PBT and vPvB assessment

Component	
methyl acetate (79-20-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
n-butyl acetate (123-86-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
acetone (67-64-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
trizinc bis(orthophosphate) (7779-90-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Xylene (1330-20-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Ethylbenzene (100-41-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number or ID number

 UN-No. (ADR)
 : UN 1950

 UN-No. (IMDG)
 : UN 1950

 UN-No. (IATA)
 : UN 1950

 UN-No. (ADN)
 : UN 1950

 UN-No. (RID)
 : UN 1950

14.2. UN proper shipping name

Proper Shipping Name (ADR) : AEROSOLS
Proper Shipping Name (IMDG) : AEROSOLS
Proper Shipping Name (IATA) : Aerosols, flammable
Proper Shipping Name (ADN) : AEROSOLS
Proper Shipping Name (RID) : AEROSOLS

Transport document description (ADR) : UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS

Transport document description (IMDG) : UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS

Transport document description (IATA) : UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS

Transport document description (ADN) : UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS Transport document description (RID) : UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

02/09/2020 (Issue date) EN (English) 24/29

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 2.1
Danger labels (ADR) : 2.1



IMDG

Transport hazard class(es) (IMDG) : 2.1
Danger labels (IMDG) : 2.1



IATA

Transport hazard class(es) (IATA) : 2.1
Danger labels (IATA) : 2.1



ADN

Transport hazard class(es) (ADN) : 2.1
Danger labels (ADN) : 2.1



RID

Transport hazard class(es) (RID) : 2.1
Danger labels (RID) : 2.1



14.4. Packing group

Packing group (ADR) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable
Packing group (ADN) : Not applicable
Packing group (RID) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : Yes
Marine pollutant : Yes

Other information : No supplementary information available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.6. Special precautions for user

Overland transport

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 1I
Excepted quantities (ADR) : E0
Packing instructions (ADR) : P207

Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR): MP9Transport category (ADR): 2Special provisions for carriage - Packages (ADR): V14Special provisions for carriage - Loading, unloading: CV9, CV12

and handling (ADR)

Special provisions for carriage - Operation (ADR) : S2 Tunnel restriction code (ADR) : D

Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Packing instructions (IMDG) : P207, LP200
Special packing provisions (IMDG) : PP87, L2
EmS-No. (Fire) : F-D
EmS-No. (Spillage) : S-U
Stowage category (IMDG) : None
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

Air transport

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

Inland waterway transport

Classification code (ADN) : 5F

Special provisions (ADN) : 190, 327, 344, 625

Limited quantities (ADN) : 1 L

Excepted quantities (ADN) : E0

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01, VE04

Number of blue cones/lights (ADN) : 1

Rail transport

Classification code (RID) : 5F

Special provisions (RID) : 190, 327, 344, 625

Limited quantities (RID) : 1L

Excepted quantities (RID) : E0

Packing instructions (RID) : P207, LP200

Special packing provisions (RID) : PP87, RR6, L2

Mixed packing provisions (RID) : MP9

Transport category (RID) : MP9

Special provisions for carriage – Packages (RID) : W14

Special provisions for carriage - Loading, unloading : CW9, CW12

and handling (RID)

Colis express (express parcels) (RID) : CE2 Hazard identification number (RID) : 23

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

02/09/2020 (Issue date) EN (English) 26/29

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Reference code	Applicable on	Entry title or description
3(a)	RAPTOR 1K MULTI USE PROTECTIVE COATING AEROSOL; Xylene; Ethylbenzene; methyl acetate; acetone; heptan-2-one; n-butyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	RAPTOR 1K MULTI USE PROTECTIVE COATING AEROSOL; Xylene; Ethylbenzene; reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylen e); reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate; methyl acetate; acetone; heptan-2-one; n-butyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	RAPTOR 1K MULTI USE PROTECTIVE COATING AEROSOL; reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene); reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	Xylene ; Ethylbenzene ; methyl acetate ; acetone ; heptan-2-one ; n-butyl acetate	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 598 g/l

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

02/09/2020 (Issue date) EN (English) 27/29

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 16: Other information

Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BLV	Biological limit value	
CAS-No.	Chemical Abstract Service number	
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC50	Median effective concentration	
EC-No.	European Community number	
EN	European Standard	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OEL	Occupational Exposure Limit	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
SDS	Safety Data Sheet	
vPvB	Very Persistent and Very Bioaccumulative	
WGK	Water Hazard Class	

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.